

# ILUMI BOLLARD 1000 1100LM 830 IP65 I CL. 360° ANTRACITE 24W

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	377310
Rated power of the luminaire [W]*:	24
Ingress protection:	IP65
Impact resistance:	IK10
Luminous flux [lm]*:	1100
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	antracyt
Beam angle [°]:	360
Dimensions (H/W/T/S) [mm]:	1000/fi170

## CHARACTERISTICS

The Bollard series has been designed using modern simulation methods to achieve the highest product quality. A product based on LEDs from the renowned American company CREE® IP67. The luminaire is made of aluminium. Power supply 220-240V AC. 5-year warranty. Power: 24W.

## APPLICATION

Bollard outdoor luminaires can be used to light and illuminate a wide range of locations and objects, including but not limited to:

- \* parks,
- \* gardens,
- \* monuments,
- \* squares,
- \* fountains.

# ILUMI BOLLARD 1000 1100LM 830 IP65 I CL. 360°

## ANTRACITE 24W

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	377310	Dimensions (H/W/T/S) [mm]:	1000/fi170
Rated power of the luminaire [W]:	24	Colour rendering index:	80
EAN:	5905963377310	Beam angle [°]:	360
Colour temperature [K]:	3000	Material of the body:	aluminium
Light source:	LED module	Ring material:	aluminium
Luminous flux [lm]:	1100	Ring colour:	black
Control:	ON/OFF	Impact resistance:	IK10
Supply voltage [V]:	220 - 240	Ingress protection:	IP65
Colour of the body:	antracyt	LED lifespan L90B10 [h]:	65000
Frequency [Hz]:	50 - 60	Category type:	accent lighting
Cable length [m]:	0.50	CE certificate:	<a href="#">78/2024</a>
Working temperature [°C]:	from -20 to +55	Warranty [years]:	5
Electrical protection class:	I	Manual:	<a href="#">Download PDF</a>

### LIGHT CURVES

