ILUMI SPOT M 3400LM 830 IP67 I CL. 10° BLACK ALU 30W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	377105
Rated power of the luminaire [W]*:	30
Ingress protection:	IP67
Impact resistance:	IK10
Luminous flux [lm]*:	3400
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	black
Beam angle [°]:	10
Dimensions (H/W/T/S) [mm]:	fi194

CHARACTERISTICS

The Ilumi Spot series has been designed using modern simulation methods to achieve the highest product quality. A product based on LEDs from the renowned American company CREE® IP67. The luminaire is made of ADC12 aluminium alloy. Round front. 5-year warranty. Power: 30 W.

APPLICATION

ILUMI SPOT outdoor luminaires can be used to light and illuminate a wide range of places and objects, such as, but not limited to:

- * parks,
- * gardens,
- * monuments,
- * squares,
- * fountains.

ILUMI SPOT M 3400LM 830 IP67 I CL. 10° BLACK ALU 30W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	377105
EAN:	5905963377105
Light source:	COB LED
Rated power of the luminaire [W]:	30
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	3400
Electrical protection class:	1
Colour temperature [K]:	3000
Colour rendering index:	80
Beam angle [°]:	10
Material of the body:	aluminium
Colour of the body:	black
Ring material:	aluminium

Ring colour:	black
Dimensions (H/W/T/S) [mm]:	fi194
Impact resistance:	IK10
Ingress protection:	IP67
Working temperature [°C]:	from -20 to +55
Control:	ON/OFF
Wire type:	H07RN-F 3G1
Cable length [m]:	0.50
Category type:	accent lighting
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	<u>54/2025</u>
Manual:	Download PDF

LIGHT CURVES



Card creation date: 15 April 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

