ILUMI SPOT M 3750M 840 IP67 I CL.30° BLACK ALU 30W

DETAILED CARD





TECHNICAL PARAMETERS

| Index: | 377136 |
|------------------------------------|-----------|
| Rated power of the luminaire [W]*: | 30 |
| Ingress protection: | IP67 |
| Impact resistance: | IK10 |
| Luminous flux [lm]*: | 3750 |
| Colour temperature [K]: | 4000 |
| Material of the body: | aluminium |
| Colour of the body: | black |
| Beam angle [°]: | 30 |
| Dimensions (H/W/T/S) [mm]: | fi194 |
| | |

CHARACTERISTICS

The Ilumi Spot series has been designed using modern simulation methods to achieve the highest product quality. A product based on LEDs from the renowned American company CREE® IP67. The luminaire is made of ADC12 aluminium alloy. Round front. 5-year warranty. Power: 30 W.

APPLICATION

ILUMI SPOT outdoor luminaires can be used to light and illuminate a wide range of places and objects, such as, but not limited to:

- * parks,
- * gardens,
- * monuments,
- * squares,
- * fountains.

ILUMI SPOT M 3750M 840 IP67 I CL.30° BLACK ALU 30W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Index: | 377136 |
|-----------------------------------|---------------|
| EAN: | 5905963377136 |
| Light source: | COB LED |
| Rated power of the luminaire [W]: | 30 |
| Supply voltage [V]: | 220 - 240 |
| Frequency [Hz]: | 50 - 60 |
| Luminous flux [Im]: | 3750 |
| Electrical protection class: | 1 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 80 |
| Beam angle [°]: | 30 |
| Material of the body: | aluminium |
| Colour of the body: | black |
| Ring material: | aluminium |

| Ring colour: | black |
|----------------------------|---------------------|
| Dimensions (H/W/T/S) [mm]: | fi194 |
| Impact resistance: | IK10 |
| Ingress protection: | IP67 |
| Working temperature [°C]: | from -20 to +55 |
| Control: | ON/OFF |
| Wire type: | H07RN-F 3G4 |
| Cable length [m]: | 0.50 |
| Category type: | accent lighting |
| LED lifespan L90B10 [h]: | 60000 |
| Warranty [years]: | 5 |
| CE certificate: | <u>54/2025</u> |
| Manual: | <u>Download PDF</u> |

LIGHT CURVES



Card creation date: 15 April 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

