ILUMI SPOT S 1390LM 830 IP67 I CL. 10° BLACK ALU 17W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	377143
Rated power of the luminaire [W]*:	17
Ingress protection:	IP67
Impact resistance:	IK10
Luminous flux [lm]*:	1390
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	black
Beam angle [°]:	10
Dimensions (H/W/T/S) [mm]:	fi130

CHARACTERISTICS

The Ilumi Spot series has been designed using modern simulation methods to achieve the highest product quality. A product based on LEDs from the renowned American company CREE® IP67. The luminaire is made of ADC12 aluminium alloy. Round front. 5-year warranty. Power: 17W.

APPLICATION

ILUMI SPOT outdoor luminaires can be used to light and illuminate a wide range of places and objects, such as, but not limited to:

- * parks,
- * gardens,
- * monuments,
- * squares,
- * fountains.

ILUMI SPOT S 1390LM 830 IP67 I CL. 10° BLACK ALU 17W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	17
Index:	377143
Colour temperature [K]:	3000
EAN:	5905963377143
Luminous flux [lm]:	1390
Light source:	COB LED
Colour of the body:	black
Beam angle [°]:	10
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Dimensions (H/W/T/S) [mm]:	fi130
Electrical protection class:	1
Colour rendering index:	80
Material of the body:	aluminium

Ring material:	aluminium
Ring colour:	black
Impact resistance:	IK10
Ingress protection:	IP67
Working temperature [°C]:	from -20 to +55
Control:	ON/OFF
Wire type:	H07RN-F 3G4
Cable length [m]:	0.50
Category type:	accent lighting
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	<u>54/2025</u>
Manual:	Download PDF

LIGHT CURVES



Card creation date: 05 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

