ILUMI GROUND XS 500LM 830 IP67 I CL. 10° SILVER ALU 5W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	377204
Index:	377204

Rated power of the luminaire [W]*: 5

Ingress protection: IP67

Impact resistance: IK10

Luminous flux [lm]*: 500

Colour temperature [K]: 3000

Colour rendering index: 80

Material of the body: aluminium

Colour of the body: silver

Beam angle [°]: 10

CHARACTERISTICS

The llumi Ground series was designed for the most demanding customers looking for customised and economical solutions. The body of the luminaire is made of cast aluminium, which has enabled a significant reduction in weight and price. A mounting box is included.

APPLICATION

The luminaires are ideal for illuminating garden or park spaces. Due to their lightweight construction, they are easy to install on external walls. The llumi Ground luminaire can be used to illuminate a wide range of spaces and objects, such as parks, gardens, terraces, squares, premises and plants.



ILUMI GROUND XS 500LM 830 IP67 I CL. 10° SILVER ALU 5W


DETAILED CARD

TECHNICAL PARAMETERS TABLE


Rated power of the luminaire [W]:	5
Index:	377204
Colour temperature [K]:	3000
EAN:	5905963377204
Luminous flux [lm]:	500
Light source:	COB LED
Version:	XS
Beam angle [°]:	10
Supply voltage [V]:	220 - 240
Dimensions (H/W/T/S) [mm]:	fi92
Frequency [Hz]:	50 - 60
Electrical protection class:	1
Colour rendering index:	80
Material of the body:	aluminium

Colour of the body:	silver
Ring material:	SST
Ring colour:	silver
Impact resistance:	IK10
Ingress protection:	IP67
Working temperature [°C]:	from -20 to +55
Control:	ON/OFF
Wire type:	H07RN-F 3G4
Cable length [m]:	0.50
Category type:	accent lighting
LED lifespan L90B10 [h]:	60000
Warranty [years]:	5
CE certificate:	80/2024
Manual:	Download PDF

LIGHT CURVES



TECHNICAL PICTURES



Card creation date: 30 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

