

# OCULUS LED XS ECO BLACK RAL9005 215X143MM 16000LM 740 I CL. IP65 120D (100W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	744662
<b>Ingress protection:</b>	IP65
<b>Impact resistance:</b>	IK08
<b>Rated power of the luminaire [W]*:</b>	100
<b>Luminous flux [lm]*:</b>	16000
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>70
<b>SDCM:</b>	≤ 3
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	B

## CHARACTERISTICS

Oculus LED XS ECO is a HIGH-BAY luminaire made using LED technology. It is the smallest representative of the renowned OCULUS LED series, with dimensions optimised for maximum output from a body made of die-cast aluminium, powder-coated in black or grey. The passive cooling system and the isolated power supply (black) have a positive effect on the thermal management of the lamp, its service life and the maintenance of the highest performance. LED modules with a high luminous efficacy (up to 165 lm/W) ensure that the required lighting levels are achieved while saving energy and reducing purchasing costs. The diffuser is made of tempered glass, which does not alter the optics of the light source - ensuring a general distribution of 120 degrees. The lamp is terminated with electrical cables (which require an airtight connector if the connection is to be IP65 tight). The design of the lamp is suitable for pendant mounting using the threaded, eyebolt hook supplied. The lamp should be suspended using a cord or chain dedicated to such solutions (not supplied).

## APPLICATION

The luminaire is designed for suspended mounting (using chains, cables, etc.) indoors, even in high humidity (IP65). It is ideal for use in factories and production halls as well as large-scale warehouses and logistics centres.

# OCULUS LED XS ECO BLACK RAL9005 215X143MM


## 16000LM 740 I CL. IP65 120D (100W)

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	100	Material of the body:	aluminium
Index:	744662	Working temperature [°C]:	from -25 to +35
Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	143/215/215
EAN:	5905963744662	Impact resistance:	IK08
Luminous flux [lm]:	16000	Ingress protection:	IP65
Light source:	LED	LED lifespan L70B50 [h]:	154500
Supply voltage [V]:	220-240	LED lifespan L80B20 [h]:	96000
Energy efficiency class:	B	LED lifespan L90B10 [h]:	45000
Frequency [Hz]:	50-60	Number on the palette [pcs]:	90
Luminous efficacy [lm/W]:	160	Net weight [kg]:	1.700
Electrical protection class:	I	Light distribution type:	symmetric
Colour rendering index:	>70	Remarks:	RAL9005
SDCM:	≤ 3	Warranty [years]:	5
Beam angle [°]:	120	CE certificate:	<a href="#">83/2024</a>
Surge protection [kV]:	1	Manual:	<a href="#">Download PDF</a>
Diffuser material:	glass	Plik LDT:	<a href="#">Download</a>
Colour of the body:	black		


### LIGHT CURVES



Card creation date: 11 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 83/2024