

OCULUS LED XS ECO BLACK RAL9005 215X143MM 16000LM 740 I CL. IP65 120D (100W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	744662
Ingress protection:	IP65
Impact resistance:	IK08
Rated power of the luminaire [W]*:	100
Luminous flux [lm]*:	16000
Colour temperature [K]:	4000
Colour rendering index:	>70
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	B

CHARACTERISTICS

Oculus LED XS ECO is a HIGH-BAY luminaire made using LED technology. It is the smallest representative of the renowned OCULUS LED series, with dimensions optimised for maximum output from a body made of die-cast aluminium, powder-coated in black or grey. The passive cooling system and the isolated power supply (black) have a positive effect on the thermal management of the lamp, its service life and the maintenance of the highest performance. LED modules with a high luminous efficacy (up to 165 lm/W) ensure that the required lighting levels are achieved while saving energy and reducing purchasing costs. The diffuser is made of tempered glass, which does not alter the optics of the light source - ensuring a general distribution of 120 degrees. The lamp is terminated with electrical cables (which require an airtight connector if the connection is to be IP65 tight). The design of the lamp is suitable for pendant mounting using the threaded, eyebolt hook supplied. The lamp should be suspended using a cord or chain dedicated to such solutions (not supplied).

APPLICATION

The luminaire is designed for suspended mounting (using chains, cables, etc.) indoors, even in high humidity (IP65). It is ideal for use in factories and production halls as well as large-scale warehouses and logistics centres.

OCULUS LED XS ECO BLACK RAL9005 215X143MM


16000LM 740 I CL. IP65 120D (100W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	744662	Diffuser material:	glass
EAN:	5905963744662	Material of the body:	aluminium
Light source:	LED	Colour of the body:	black
Rated power of the luminaire [W]:	100	Dimensions (H/W/T/S) [mm]:	143/215/215
Luminous flux [lm]:	16000	Impact resistance:	IK08
Supply voltage [V]:	220-240	Ingress protection:	IP65
Frequency [Hz]:	50-60	Working temperature [°C]:	from -25 to +35
Luminous efficacy [lm/W]:	160	Number on the palette [pcs]:	90
Energy efficiency class:	B	Net weight [kg]:	1.700
Electrical protection class:	I	Light distribution type:	symmetric
Colour temperature [K]:	4000	Remarks:	RAL9005
Colour rendering index:	>70	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	83/2024
Beam angle [°]:	120	Manual:	Download PDF
Surge protection [kV]:	1		

LIGHT CURVES



Card creation date: 11 September 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 83/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl