

TYTAN STEEL LED 600MM 3250LM 840 IP66 120D 20W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	596407
Ingress protection:	IP66
Impact resistance:	IK06
Rated power of the luminaire [W]*:	20
Luminous flux [lm]*:	3250
Colour temperature [K]:	4000
Material of the body:	coated steel
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	matrix led

CHARACTERISTICS

The Tytan Steel LED reflects an innovative approach to the classic hermetic luminaire that combines functionality with aesthetics. All the technical advantages of a traditional hermetic luminaire are encapsulated in a sleek, low profile, giving the lamp a modern design. Thanks to its advanced optics, the Tytan Steel LED will be suitable for both the simplest applications and demanding industrial solutions. The product is characterised by exceptional ease of installation, low purchase and operating costs (169 lm/W). The reliable components used in the lamp minimise the need for servicing. The Tytan Steel LED is made of steel for exceptional durability and, thanks to its U-shaped profile design, retains the lightness typical of plastic luminaires, making it easy to install and not weighing down load-bearing structures. The Tytan Steel LED is the optimum combination of functionality and economy, ideal for a wide range of applications.

APPLICATION

The multi-purpose LED luminaire is designed for use in areas with high dust- and water-tightness requirements. It is particularly recommended for the illumination of industrial and warehouse halls, garages, car parks (underground and multi-storey), public facilities including hospitals, educational and educational facilities, retail and service facilities, transport terminals and underground passages. The lamp is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-efficient LED solutions. Its design is suitable for surface-mounted and suspended installation.

TYTAN STEEL LED 600MM 3250LM 840 IP66 120D 20W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	596407	Diffuser type:	matrix led
EAN:	5905963596407	Material of the body:	coated steel
Light source:	LED module	Colour of the body:	white
Rated power of the luminaire [W]:	20	Remarks:	RAL9010
Luminous flux [lm]:	3250	Dimensions (H/W/T/S) [mm]:	600/57/45
Supply voltage [V]:	220-240	Mounting dimensions [mm]:	520
Frequency [Hz]:	50-60	Impact resistance:	IK06
Luminous efficacy [lm/W]:	163	Ingress protection:	IP66
Energy efficiency class:	B	Mounting version:	surface, suspended
Electrical protection class:	I	Number on the palette [pcs]:	165
Colour temperature [K]:	4000	Net weight [kg]:	0.850
Colour rendering index:	80	Light distribution type:	symmetric
SDCM:	≤ 3	Working temperature [°C]:	from +35 to -20
LED lifespan L70B50 [h]:	140000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L80B20 [h]:	88000	Warranty [years]:	5
LED lifespan L90B10 [h]:	42000	CE certificate:	73/2025
Beam angle [°]:	120	Manual:	Download PDF
Surge protection [kV]:	2	Plik LDT:	Download
Diffuser material:	PC		

LIGHT CURVES



TYTAN STEEL LED 600MM 3250LM 840 IP66 120D 20W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
80001264	Tytan Steel protection grid 1188mm RAL9003
80001265	Protection grid Sensor Hytronik HIM84 RAL 9003
598432	Tytan Steel - suspension bracket (set)



Tytan Steel protection grid 1188mm
RAL9003 (80001264)



Protection grid Sensor Hytronik HIM84
RAL 9003 (80001265)

Card creation date:15 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric andelectronic waste equipment regulations (WEEE).



Certificate CE - Nr: 73/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl