

TYTAN STEEL LED 1188MM 12000LM 840 IP65 120D 73W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	596544
Ingress protection:	IP65
Impact resistance:	IK06
Rated power of the luminaire [W]*:	73
Luminous flux [lm]*:	12000
Colour temperature [K]:	4000
Material of the body:	coated steel
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	matrix led

CHARACTERISTICS

The Tytan Steel LED reflects an innovative approach to the classic hermetic luminaire that combines functionality with aesthetics. All the technical advantages of a traditional hermetic luminaire are encapsulated in a sleek, low profile, giving the lamp a modern design. Thanks to its advanced optics, the Tytan Steel LED will be suitable for both the simplest applications and demanding industrial solutions. The product is characterised by exceptional ease of installation, low purchase and operating costs (169 lm/W). The reliable components used in the lamp minimise the need for servicing. The Tytan Steel LED is made of steel for exceptional durability and, thanks to its U-shaped profile design, retains the lightness typical of plastic luminaires, making it easy to install and not weighing down load-bearing structures. The Tytan Steel LED is the optimum combination of functionality and economy, ideal for a wide range of applications.

APPLICATION

The multi-purpose LED luminaire is designed for use in areas with high dust- and water-tightness requirements. It is particularly recommended for the illumination of industrial and warehouse halls, garages, car parks (underground and multi-storey), public facilities including hospitals, educational and educational facilities, retail and service facilities, transport terminals and underground passages. The lamp is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-efficient LED solutions. Its design is suitable for surface-mounted and suspended installation.

TYTAN STEEL LED 1188MM 12000LM 840 IP65 120D 73W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	73	Colour of the body:	white
Index:	596544	Diffuser material:	PC
Colour temperature [K]:	4000	Diffuser type:	matrix led
EAN:	5905963596544	Material of the body:	coated steel
Luminous flux [lm]:	12000	Remarks:	RAL9010
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	1188/57/45
Beam angle [°]:	120	Mounting dimensions [mm]:	520
Supply voltage [V]:	220-240	Impact resistance:	IK06
Light distribution type:	symmetric	Ingress protection:	IP65
Frequency [Hz]:	50-60	Mounting version:	surface, suspended
Luminous efficacy [lm/W]:	164	Number on the palette [pcs]:	110
Energy efficiency class:	B	Net weight [kg]:	1.350
Electrical protection class:	I	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	86/2024
LED lifespan L70B50 [h]:	140000	Manual:	Download PDF
LED lifespan L80B20 [h]:	88000		
LED lifespan L90B10 [h]:	42000		
Surge protection [kV]:	2		

LIGHT CURVES



Card creation date: 15 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 86/2024



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl