

# TYTAN STEEL LED 600MM 3250LM 840 IP66 LS2 120D 20W

## DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	598548
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK06
<b>Rated power of the luminaire [W]*:</b>	20
<b>Luminous flux [lm]*:</b>	3250
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	coated steel
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	matrix led

## CHARACTERISTICS

The Tytan Steel LED reflects an innovative approach to the classic hermetic luminaire that combines functionality with aesthetics. All the technical advantages of a traditional hermetic luminaire are encapsulated in a sleek, low profile, giving the lamp a modern design. Thanks to its advanced optics, the Tytan Steel LED will be suitable for both the simplest applications and demanding industrial solutions. The product is characterised by exceptional ease of installation, low purchase and operating costs (169 lm/W). The reliable components used in the lamp minimise the need for servicing. The Tytan Steel LED is made of steel for exceptional durability and, thanks to its U-shaped profile design, retains the lightness typical of plastic luminaires, making it easy to install and not weighing down load-bearing structures. The Tytan Steel LED is the optimum combination of functionality and economy, ideal for a wide range of applications.

## APPLICATION

The multi-purpose LED luminaire is designed for use in areas with high dust- and water-tightness requirements. It is particularly recommended for the illumination of industrial and warehouse halls, garages, car parks (underground and multi-storey), public facilities including hospitals, educational and educational facilities, retail and service facilities, transport terminals and underground passages. The lamp is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-efficient LED solutions. Its design is suitable for surface-mounted and suspended installation.


# TYTAN STEEL LED 600MM 3250LM 840 IP66 LS2 120D 20W

## DETAILED CARD

### TECHNICAL PARAMETERS TABLE

Index:	598548	Material of the body:	coated steel
EAN:	5905963598548	Colour of the body:	white
Light source:	LED module	Remarks:	RAL9010
Rated power of the luminaire [W]:	20	Dimensions (H/W/T/S) [mm]:	600/57/45
Luminous flux [lm]:	3250	Mounting dimensions [mm]:	520
Supply voltage [V]:	220-240	Impact resistance:	IK06
Frequency [Hz]:	50-60	Ingress protection:	IP66
Luminous efficacy [lm/W]:	163	Mounting version:	surface, suspended
Energy efficiency class:	B	Wire type:	5x1,5
Electrical protection class:	I	Through wiring:	LS2
Colour temperature [K]:	4000	Number on the palette [pcs]:	165
Color rendering index (Ra) >:	80	Net weight [kg]:	1
SDCM:	3	Light distribution type:	symmetric
LED lifespan L70B50 [h]:	140000	Working temperature [°C]:	from +35 to -20
LED lifespan L80B20 [h]:	88000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L90B10 [h]:	42000	Warranty [years]:	5
Beam angle [°]:	120	CE certificate:	<a href="#">73/2025</a>
Surge protection [kV]:	2	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PC	Plik LDT:	<a href="#">Download</a>
Diffuser type:	matrix led		

### LIGHT CURVES




# TYTAN STEEL LED 600MM 3250LM 840 IP66 LS2 120D 20W

## DETAILED CARD

### ACCESSORIES AVAILABLE

index	Name
598906	Tytan Steel protection grid 1188mm RAL9003
598913	Protection grid Sensor Hytronik HIM84 RAL 9003
598432	Tytan Steel - suspension bracket (set)



Tytan Steel protection grid 1188mm  
RAL9003 (598906)



Protection grid Sensor Hytronik HIM84  
RAL 9003 (598913)

Card creation date: 03 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 73/2025