TYTAN STEEL LED PRO 1188MM 15150LM 840 IP66 DALI MW 80W

DETAILED CARD





TECHNICAL PARAMETERS

Index: 596186

Ingress protection: IP66

Impact resistance: IK06

Rated power of the luminaire [W]*: 80

Luminous flux [lm]*: 15150

Colour temperature [K]: 4000

Material of the body: coated steel

Colour of the body: white

Diffuser material: PC

Diffuser type: matrix led

CHARACTERISTICS

Tytan Steel LED Pro is an innovative solution in the category of classic hermetic luminaires, combining functionality with modern design. All the technical advantages of a traditional hermetic are enclosed in an elegant, low-profile housing, enriched with advanced optics that make the Tytan Steel LED Pro a versatile luminaire. It will prove its worth in both the simplest applications and advanced industrial solutions. The product is distinguished by very fast installation and low purchase and operating costs (192 lm/W). The reliable components used in the lamp minimise the need for servicing. The Tytan Steel LED Pro lamp is made of steel for exceptional durability and, thanks to its U-shaped profile design, retains the lightness typical of plastic luminaires, making it easy to install and not weighing down load-bearing structures. Tytan Steel LED Pro is the ideal economic and functional solution for a wide range of applications.

APPLICATION

The multi-purpose LED luminaire is designed for use in areas with high dust- and water-tightness requirements. It is particularly recommended for the illumination of industrial and warehouse halls, garages, car parks (underground and multistorey), public facilities including hospitals, educational and educational facilities, retail and service facilities, transport terminals and underground passages. The lamp is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-efficient LED solutions. Its design is suitable for surface-mounted and suspended installation.



TYTAN STEEL LED PRO 1188MM 15150LM 840 IP66 DALI MW 80W


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	596186
EAN:	5905963596186
Light source:	LED module
Rated power of the luminaire [W]:	80
Luminous flux [lm]:	15150
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	189
Energy efficiency class:	А
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	140000
LED lifespan L80B20 [h]:	88000
LED lifespan L90B10 [h]:	42000
Surge protection [kV]:	1
Diffuser material:	PC
Diffuser type:	matrix led

Material of the body:	coated steel
Colour of the body:	white
Remarks:	RAL9010
Dimensions (H/W/T/S) [mm]:	1188/57/45
Mounting dimensions [mm]:	520
Impact resistance:	IK06
Ingress protection:	IP66
Mounting version:	surface, suspended
DIMM DALI:	yes
Number on the palette [pcs]:	110
Net weight [kg]:	1.350
Beam angle [°]:	90
Light distribution type:	MW
Working temperature [°C]:	from +35 to -20
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Warranty [years]:	5
CE certificate:	140/2025
Manual:	Download PDF
Plik LDT:	Download

LIGHT CURVES






TYTAN STEEL LED PRO 1188MM 15150LM 840 IP66 DALI MW 80W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
598906	Tytan Steel protection grid 1188mm RAL9003
598913	Protection grid Sensor Hytronik HIM84 RAL 9003
598432	Tytan Steel - suspension bracket (set)



Tytan Steel protection grid 1188mm RAL9003 (598906)



Protection grid Sensor Hytronik HIM84 RAL 9003 (598913)

Card creation date: 04 November 2025

LIGHTING

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



