

TYTAN STEEL LED PRO 600MM 4850LM 840 IP66 LS2(2,5) VN 28W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|--------------|
| Index: | 596902 |
| Ingress protection: | IP66 |
| Impact resistance: | IK06 |
| Rated power of the luminaire [W]*: | 28 |
| Luminous flux [lm]*: | 4850 |
| Colour temperature [K]: | 4000 |
| Material of the body: | coated steel |
| Colour of the body: | white |
| Diffuser material: | PC |
| Diffuser type: | matrix led |

CHARACTERISTICS

Tytan Steel LED Pro is an innovative solution in the category of classic hermetic luminaires, combining functionality with modern design. All the technical advantages of a traditional hermetic are enclosed in an elegant, low-profile housing, enriched with advanced optics that make the Tytan Steel LED Pro a versatile luminaire. It will prove its worth in both the simplest applications and advanced industrial solutions. The product is distinguished by very fast installation and low purchase and operating costs (192 lm/W). The reliable components used in the lamp minimise the need for servicing. The Tytan Steel LED Pro lamp is made of steel for exceptional durability and, thanks to its U-shaped profile design, retains the lightness typical of plastic luminaires, making it easy to install and not weighing down load-bearing structures. Tytan Steel LED Pro is the ideal economic and functional solution for a wide range of applications.

APPLICATION

The multi-purpose LED luminaire is designed for use in areas with high dust- and water-tightness requirements. It is particularly recommended for the illumination of industrial and warehouse halls, garages, car parks (underground and multi-storey), public facilities including hospitals, educational and educational facilities, retail and service facilities, transport terminals and underground passages. The lamp is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-efficient LED solutions. Its design is suitable for surface-mounted and suspended installation.


TYTAN STEEL LED PRO 600MM 4850LM 840 IP66 LS2(2,5) VN 28W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|--|---|
| Index: | 596902 | Remarks: | RAL9010 |
| EAN: | 5905963596902 | Dimensions (H/W/T/S) [mm]: | 600/57/45 |
| Light source: | LED module | Mounting dimensions [mm]: | 520 |
| Rated power of the luminaire [W]: | 28 | Impact resistance: | IK06 |
| Luminous flux [lm]: | 4850 | Ingress protection: | IP66 |
| Supply voltage [V]: | 220-240 | Mounting version: | surface, suspended |
| Frequency [Hz]: | 50-60 | Wire type: | 5x2,5 |
| Luminous efficacy [lm/W]: | 173 | Through wiring: | LS2 (2.5) |
| Energy efficiency class: | B | Number on the palette [pcs]: | 165 |
| Electrical protection class: | I | Net weight [kg]: | 1 |
| Colour temperature [K]: | 4000 | Beam angle [°]: | 30 |
| Color rendering index (Ra) >: | 80 | Light distribution type: | VN |
| SDCM: | 3 | Working temperature [°C]: | from +35 to -20 |
| LED lifespan L70B50 [h]: | 140000 | Photobiological safety: | Risk Group 1 (no photobiological hazard under normal behavioral limitation) |
| LED lifespan L80B10 [h]: | 88000 | Warranty [years]: | 5 |
| LED lifespan L90B10 [h]: | 42000 | CE certificate: | 74/2025 |
| Surge protection [kV]: | 2 | ENEC Certificate: | 0470/ENEC/26 |
| Diffuser material: | PC | Environmental Product Declaration (EPD): | 869/2025 |
| Diffuser type: | matrix led | Manual: | Download PDF |
| Material of the body: | coated steel | ISO Certificates: | 9001:2015, 14001:2015, 45001:2018, 50001:2018 |
| Colour of the body: | white | Plik LDT: | Download |

LIGHT CURVES



TYTAN STEEL LED PRO 600MM 4850LM 840 IP66 LS2(2,5) VN 28W

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|--|
| 598906 | Tytan Steel protection grid 1188mm RAL9003 |
| 598913 | Protection grid Sensor Hytronik HIM84 RAL 9003 |
| 598432 | Tytan Steel - suspension bracket (set) |



Tytan Steel protection grid 1188mm
RAL9003 (598906)



Protection grid Sensor Hytronik HIM84
RAL 9003 (598913)

Card creation date: 03 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 74/2025