

TYTAN STEEL LED PRO 600MM 4650LM 840 IP66 LS2(2,5) 5P DALI DAN 28W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	598517
Ingress protection:	IP66
Impact resistance:	IK06
Rated power of the luminaire [W]*:	28
Luminous flux [lm]*:	4650
Colour temperature [K]:	4000
Material of the body:	coated steel
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	matrix led

CHARACTERISTICS

Tytan Steel LED Pro is an innovative solution in the category of classic hermetic luminaires, combining functionality with modern design. All the technical advantages of a traditional hermetic are enclosed in an elegant, low-profile housing, enriched with advanced optics that make the Tytan Steel LED Pro a versatile luminaire. It will prove its worth in both the simplest applications and advanced industrial solutions. The product is distinguished by very fast installation and low purchase and operating costs (192 lm/W). The reliable components used in the lamp minimise the need for servicing. The Tytan Steel LED Pro lamp is made of steel for exceptional durability and, thanks to its U-shaped profile design, retains the lightness typical of plastic luminaires, making it easy to install and not weighing down load-bearing structures. Tytan Steel LED Pro is the ideal economic and functional solution for a wide range of applications.

APPLICATION

The multi-purpose LED luminaire is designed for use in areas with high dust- and water-tightness requirements. It is particularly recommended for the illumination of industrial and warehouse halls, garages, car parks (underground and multi-storey), public facilities including hospitals, educational and educational facilities, retail and service facilities, transport terminals and underground passages. The lamp is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-efficient LED solutions. Its design is suitable for surface-mounted and suspended installation.


TYTAN STEEL LED PRO 600MM 4650LM 840 IP66 LS2(2,5) 5P DALI DAN 28W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	598517	Colour of the body:	white
EAN:	5905963598517	Remarks:	RAL9010
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	600/57/45
Rated power of the luminaire [W]:	28	Impact resistance:	IK06
Luminous flux [lm]:	4650	Ingress protection:	IP66
Supply voltage [V]:	220-240	Mounting version:	surface, suspended
Frequency [Hz]:	50-60	DIMM DALI:	yes
Luminous efficacy [lm/W]:	166	Wire type:	5x2,5
Energy efficiency class:	B	Through wiring:	LS2 (2.5)
Electrical protection class:	I	Number on the palette [pcs]:	165
Colour temperature [K]:	4000	Net weight [kg]:	1.100
Colour rendering index:	80	Beam angle [°]:	butterfly
SDCM:	≤ 3	Light distribution type:	DAN
LED lifespan L70B50 [h]:	140000	Working temperature [°C]:	from +35 to -20
LED lifespan L80B20 [h]:	88000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L90B10 [h]:	42000	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	74/2025
Diffuser type:	matrix led	Manual:	Download PDF
Material of the body:	coated steel	Plik LDT:	Download

LIGHT CURVES



TYTAN STEEL LED PRO 600MM 4650LM 840 IP66 LS2(2,5) 5P DALI DAN 28W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
80001264	Tytan Steel protection grid 1188mm RAL9003
80001265	Protection grid Sensor Hytronik HIM84 RAL 9003
598432	Tytan Steel - suspension bracket (set)



Tytan Steel protection grid 1188mm
RAL9003 (80001264)



Protection grid Sensor Hytronik HIM84
RAL 9003 (80001265)

Card creation date:15 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric andelectronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 74/2025