

TERRACO DIR/IND LED ALU 390LM PLX IP54 I CL. 840 17W GRAPHITE

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|------------|
| Light source: | LED module |
| Rated power of the luminaire [W]*: | 17 |
| Luminous flux [lm]*: | 390 |
| Energy efficiency class: | B |
| Electrical protection class: | I |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| Exchangeable source: | yes |
| Material of the body: | aluminium |
| Impact resistance: | IK04 |

CHARACTERISTICS

Terraco LED is a modernistic lamp distinguished by its interesting minimalist design. The powder-coated steel body of the lamp is available in three color versions: silver, graphite, white and black. The multitude of versions with different luminous surfaces makes it possible to use it in numerous places and in different ways: vertically and horizontally. Mounted on the facade of a building, it can shine down, down and up, as well as sideways. It features a high IP54 waterproof rating. It is designed for surface mounting.

APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements.

The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.

TERRACO DIR/IND LED ALU 390LM PLX IP54 I CL. 840 17W GRAPHITE

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|---------------|-----------------------------------|------------------------------|
| Index: | 995941 | Exchangeable source: | yes |
| EAN: | 5905963995941 | Diffuser material: | PMMA |
| Light source: | LED module | Diffuser type: | MAT |
| Rated power of the luminaire [W]: | 17 | Diffuser colour: | white |
| Luminous flux [lm]: | 390 | Material of the body: | aluminium |
| AC voltage range [V]: | 220 - 240 | Colour of the body: | graphite |
| Frequency [Hz]: | 50-60 | Dimensions (H/W/T/S) [mm]: | 260/110/100 |
| Luminous efficacy [lm/W]: | 24 | Impact resistance: | IK04 |
| Energy efficiency class: | B | Ingress protection: | IP54 |
| Electrical protection class: | I | Mounting version: | surface |
| Colour temperature [K]: | 4000 | Working temperature [°C]: | from -25 to +35 |
| Colour rendering index: | >80 | CE certificate: | 184/2023 |
| SDCM: | ≤ 4 | Manual: | Download PDF |
| LED lifespan L70B50 [h]: | 134000 | Category type: | spotlight |
| LED lifespan L80B20 [h]: | 86000 | Warranty [years]: | 5 |
| LED lifespan L90B10 [h]: | 46000 | | |

TECHNICAL DETAILS



Dir/Ind

Card creation date: 17 October 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 184/2023

 **LENA**
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl