TERRACO DIR/IND LED ALU 470LM PLX IP54 I CL. 840 17W GREY

DETAILED CARD





TECHNICAL PARAMETERS

Index: 99	95934
-----------	-------

Light source: LED module

Rated power of the luminaire [W]*: 17

Luminous flux [lm]*: 480

Energy efficiency class: G

Electrical protection class:

Colour temperature [K]: 4000

Color rendering index (Ra) >: 80

Exchangeable source: yes

Material of the body: aluminium

CHARACTERISTICS

Terraco LED is a modernist luminaire distinguished by its interesting minimalist design. The powder-coated aluminium body of the lamp is available in four colour versions: grey, graphite, white and black. The multitude of versions with different luminous surfaces allows it to be used in a variety of places and in different ways: vertically and horizontally. Installed on a building façade, it can shine downwards, upwards and sideways. It has a high ingress protection rating of IP54. It is designed for surface mounting.

APPLICATION

The Terraco LED lamp will be particularly suitable as outdoor facade lighting, terrace lighting, and balcony lighting. Small dimensions increase the range of its applications - it can illuminate alcoves or hard-to-reach places. Terraco lamps can also be used in the interiors of buildings and arranged in a variety of ways on the wall to form interesting lighting arrangements. The lamp allows to realize a large number of interesting lighting concepts. It is used to illuminate contemporary architecture.



TERRACO DIR/IND LED ALU 470LM PLX IP54 I CL. 840 17W GREY

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	995934
EAN:	5905963995934
Light source:	LED module
Rated power of the luminaire [W]:	17
Luminous flux [lm]:	480
AC voltage range [V]:	220 - 240
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	29
Energy efficiency class:	G
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	4
LED lifespan L70B50 [h]:	134000
LED lifespan L80B20 [h]:	86000
LED lifespan L90B10 [h]:	46000
Light distribution type:	DIR/IND

	•
Optics:	general
Exchangeable source:	yes
Diffuser material:	PMMA
Diffuser type:	matt
Diffuser colour:	white
Material of the body:	aluminium
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	260/110/100
Impact resistance:	IK04
Ingress protection:	IP54
Mounting version:	surface
Working temperature [°C]:	from -25 to +35
Warranty [years]:	5
CE certificate:	90/2025
Manual:	Download PDF
Category of application:	architectural
Plik LDT:	Download

TECHNICAL DETAILS



Dir/Ind

Card creation date: 19 September 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

