

SKVER S R 4125LM 740 RM7 WJ IP66 II CL. DALI B 0 (26W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	421716
Ingress protection:	IP66
Impact resistance:	IK10
Rated power of the luminaire [W]*:	26
Luminous flux [lm]*:	4125
Colour temperature [K]:	4000
Colour rendering index:	> 70
Electrical protection class:	II
Optics:	RM7

CHARACTERISTICS

Modular suspended innovative park and city LED luminaire with tool-free access to the equipment chamber, equipped with a tool-free service plate compliant with the ZhagaBook 13 and 15 standard. Made of pressure-formed aluminum, equipped with a PC lampshade, characterized by the ULR coefficient, increased resistance to mechanical impacts and an increased color rendering index. The luminaire is available in variants with an omnidirectional and directed way of lighting. The luminaire allows the use of dedicated functional accessories that adapt the luminaire to the needs, both in terms of mounting method, lighting method and design.

APPLICATION

External areas of places such as: town halls, libraries, city offices, healthcare facilities, schools, preschools, public gardens, streets, sidewalks, recreational areas: sports fields, playgrounds, bike paths, historical sites, old towns.

SKVER S R 4125LM 740 RM7 WJ IP66 II CL. DALI B 0 (26W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	421716	Dimensions (H/W/T/S) [mm]:	316/363/363
Rated power of the luminaire [W]:	26	Mounting dimensions [mm]:	42/25,4/19,2
EAN:	5905963421716	Impact resistance:	IK10
Luminous flux [lm]:	4125	Ingress protection:	IP66
Category type:	street lighting	Mounting version:	suspended
Colour temperature [K]:	4000	Tilt angle adjustment [°]:	no
Luminous efficacy [lm/W]:	159	Lateral surface (SCx) [m2]:	0.062
Light source:	LED module	Working temperature [°C]:	from -40 to +50
Energy efficiency class:	B	DIMM DALI:	yes
Supply voltage [V]:	220 - 240	Control:	Yes + 5-stage power reduction
Frequency [Hz]:	50 - 60	Protection type:	NTC + ESD
Electrical protection class:	II	Net weight [kg]:	6
Colour rendering index:	> 70	Wire type:	HO7 RNF-2x1
SDCM:	≤ 4	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser material:	PC	Technical Warranty:	5 with the possibility of extension to 10
Diffuser type:	transparent	ENEC Certificate:	0351/ENEC/24/M1; 0121/ENEC+24/M2
Optics material:	PMMA	CE certificate:	09/2025
Optics:	RM7	Zhaga-D4i:	ZG430121062024
Material of the body:	powder coated aluminium	Environmental Product Declaration (EPD):	683/2024
Colour of the body:	black	Manual:	Download PDF
		LED lifespan L95B10 [h]:	100000

LIGHT CURVES



SKVER S R 4125LM 740 RM7 WJ IP66 II CL. DALI B 0 (26W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
449017	Drilling pattern
804427	SKVER R male adapter thread M20x40 (pitch 2.5)
804328	SKVER R male adapter thread ¾ inch x 40 (gas)
804434	SKVER R male adapter thread 1 inch x40 (gas)
804335	SKVER R female adapter thread ¾ inch x 40 (gas)
804441	SKVER R female adapter thread 1 inch x40 (gas)



Drilling pattern (449017)



SKVER R male adapter thread M20x40 (pitch 2.5) (804427)



SKVER R male adapter thread ¾ inch x 40 (gas) (804328)



SKVER R male adapter thread 1 inch x40 (gas) (804434)



SKVER R female adapter thread ¾ inch x 40 (gas) (804335)



SKVER R female adapter thread 1 inch x40 (gas) (804441)

Card creation date: 12 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 09/2025