TERRA 2 LED P IOT PIR BT 595X595MM X2 2600LM 840 WHITE MAT (20W)

DETAILED CARD





TECHNICAL PARAMETERS

Rated power of the luminaire [W]*: 20

Luminous flux [lm]*: 2600

F **Energy efficiency class:**

Electrical protection class:

4000 Colour temperature [K]:

Beam angle [°]: 90

CHARACTERISTICS

Recessed square LED luminaire with high total luminous Flux. Made of powdercoated white steel sheet. The luminaire has a patented HE reflector installed, which ensures efficiency and effectively eliminates glare. Available mounting versions: surface mounted, surface mounted on neodymium magnets (magnet ver. / N-MAG), flush-mounted in modular or KG ceilings (using an adapter), or suspended. In the surface-mounted version, solutions influencing the speed and safety of installation were used. In addition, the versions with neodymium magnets shorten the installation time of surface-mounted versions to an absolute minimum.

IoT characteristics

IoT BT CAS DALI a built-in BT CAS module that allows you to program functions in the CASAMBI app and control in real time, and a DALI driver that allows you to dim

IoT BT HYT PWM BT HYT module (built into the driver) allowing you to program functions in the Lena Lighting Clue app and control in real time, and a **PWM** driver for dimming the light source.

IoT BT PIR HYT DALI a built-in **BT HYT** module that allows you to program functions in the Lena Lighting Clue app and control in real time; **PIR** motion and daylight sensor and **DALI** driver for dimming the light source.

IOT BT PIR HYT PWM BT HYT module (built into the driver) allowing for programming functions in the Lena Lighting Clue application and real-time control; PIR motion and daylight sensor and PWM driver for dimming the light source

IoT DS HYT 1-10V a built-in DS daylight sensor and a 1-10V driver for dimming the light source.

APPLICATION

General-purpose recessed luminaire for indoor application in offices or other utility rooms. Appropriate as the main light source even when the work requires eyesight concentration.

UGR <19

Unified Glare Rating is an indicator characterizing glare. The lower the Unified Lighting Rating Index (UGR), the lower the glare. In the case of luminaires designed for office spaces, UGR <19, among, others improves the comfort of work, reduces errors and fatigue. The UGR value also depends on many factors characterizing the room and the location of the observer. Special computer programs should be used to precisely determine the degree of glare for specific conditions.



TERRA 2 LED P IOT PIR BT 595X595MM X2 2600LM 840 WHITE MAT (20W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	224256	
Light source:	LED module	
Rated power of the luminaire [W]:	20	
Luminous flux [Im]:	2600	
Supply voltage [V]:	220 - 240	
Frequency [Hz]:	50 - 60	
Luminous efficacy [lm/W]:	102	
Energy efficiency class:	Е	
Electrical protection class:	II	
Colour temperature [K]:	4000	
Color rendering index (Ra) >:	80	
SDCM:	3	
Power factor:	0.96	
LED lifespan L70B50 [h]:	132000	
LED lifespan L80B20 [h]:	84000	
LED lifespan L90B10 [h]:	42000	

D	00	
Beam angle [°]:	90	
Efficiency of the luminaire:	0.71	
Optics:	HE	
Material of the body:	powder coated steel	
Colour of the body:	white mat	
Dimensions (H/W/T/S) [mm]:	595/595/32	
Ingress protection:	IP20	
Mounting version:	recessed	
Working temperature [°C]:	from -20 to +35	
Number on the palette [pcs]:	40	
Net weight [kg]:	1.850	
Warranty [years]:	5	
Category type:	troffers	
PIR:	yes	
CE certificate:	445/2023	
Product line:	2x1	

LIGHT CURVES





TERRA 2 LED P IOT PIR BT 595X595MM X2 2600LM 840 WHITE MAT (20W)

DETAILED CARD

TECHNICAL DETAILS



TERRA 2 LED




TERRA 2 LED P IOT PIR BT 595X595MM X2 2600LM 840 WHITE MAT (20W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)



Plasterboard recessing kit 630x630 white (steel version) (999543)

Card creation date: 18 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/-10%

