SPECTO LED EVO 595MM 1820LM PRM MAT IP40 830 (17W)

DETAILED CARD





TECHNICAL PARAMETERS

342974
IP40
IK02
15
1820
3000
80
3
E
steel

CHARACTERISTICS

Surface ceiling or wall mounted, high performance LED luminaire with compact space saving construction. Equipped with energy saving light sources LED. Powderpainted steel base, special multilayer prismatic diffuser combining high UV resistance PMMA cover and polypropylene optic system or single layer high UV resistance opal PMMA diffuser.

APPLICATION

Multi-purpose LED luminaire designed for indoor application for illuminating public use areas and corridors (administration buildings, schools and universities, health care buildings) Especially recommended for small space application or as complementary lighting. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling or wall) using included accessory installation kit.



SPECTO LED EVO 595MM 1820LM PRM MAT IP40 830 (17W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	342974
EAN:	5905963342974
Light source:	LED module
Nominal power [W]:	15
Rated power of the luminaire [W]:	17
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux [lm]:	1820
Luminous efficacy [lm/W]:	107
Energy efficiency class:	Е
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	109000
LED lifespan L80B20 [h]:	68000
LED lifespan L90B10 [h]:	33000

	1
Diffuser material:	РММА
Diffuser type:	PRM MAT
Material of the body:	steel
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	595/45/84
Mounting dimensions [mm]:	222
Impact resistance:	IK02
Ingress protection:	IP40
Mounting version:	surface
Working temperature [°C]:	from -17 to +35
Number on the palette [pcs]:	200
Net weight [kg]:	0.800
Category type:	battens
Warranty [years]:	5
CE certificate:	
Manual:	Download PDF
Plik LDT:	Download

TECHNICAL PICTURES



Card creation date: 12 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

