


SPECTO LED EVO 595MM 1950LM PRM MAT IP40 840 (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	342950
Ingress protection:	IP40
Impact resistance:	IK02
Nominal power [W]:	15
Luminous flux [lm]*:	1950
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E
Material of the body:	steel

CHARACTERISTICS

Surface ceiling or wall mounted, high performance LED luminaire with compact space saving construction. Equipped with energy saving light sources LED. Powderpainted steel base, special multilayer prismatic diffuser combining high UV resistance PMMA cover and polypropylene optic system or single layer high UV resistance opal PMMA diffuser.

APPLICATION

Multi-purpose LED luminaire designed for indoor application for illuminating public use areas and corridors (administration buildings, schools and universities, health care buildings) Especially recommended for small space application or as complementary lighting. It is appropriate for new applications as well as replacing conventional T8 & T5 fittings on energy saving LED solutions. Fitting construction adapted for surface mounting (ceiling or wall) using included accessory installation kit.

SPECTO LED EVO 595MM 1950LM PRM MAT IP40 840 (17W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	15	LED lifespan L80B20 [h]:	68000
Index:	342950	LED lifespan L90B10 [h]:	33000
Colour temperature [K]:	4000	Diffuser material:	PMMA
EAN:	5905963342950	Material of the body:	steel
Luminous flux [lm]:	1950	Colour of the body:	white
Light source:	LED module	Mounting dimensions [mm]:	222
Diffuser type:	PRM MAT	Impact resistance:	IK02
Dimensions (H/W/T/S) [mm]:	595/45/84	Ingress protection:	IP40
Rated power of the luminaire [W]:	17	Mounting version:	surface
Energy efficiency class:	E	Working temperature [°C]:	from -17 to +35
Supply voltage [V]:	220-240	Number on the palette [pcs]:	200
Frequency [Hz]:	50-60	Net weight [kg]:	0.800
Luminous efficacy [lm/W]:	115	Category type:	battens
Electrical protection class:	I	Warranty [years]:	5
Colour rendering index:	>80	CE certificate:	
SDCM:	≤ 3	Manual:	Download PDF
LED lifespan L70B50 [h]:	109000	Plik LDT:	Download

TECHNICAL PICTURES

