

# BARIS 40 LED UGR PLUS N 2625LM DALI I CL. IP20 1140MM 840 17W WHITE 60D

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	769061
<b>Ingress protection:</b>	IP20
<b>Impact resistance:</b>	IK03
<b>Rated power of the luminaire [W]*:</b>	17
<b>Luminous flux [lm]*:</b>	2625
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	white

## CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver. The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

## APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

# BARIS 40 LED UGR PLUS N 2625LM DALI I CL. IP20 1140MM 840 17W WHITE 60D

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	769061	Material of the body:	aluminium
EAN:	5905963769061	Colour of the body:	white
Light source:	LED	Dimensions (H/W/T/S) [mm]:	53/40/1140
Rated power of the luminaire [W]:	17	Mounting dimensions [mm]:	1055
Luminous flux [lm]:	2625	Impact resistance:	IK03
Supply voltage [V]:	220 - 240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous efficacy [lm/W]:	154	Working temperature [°C]:	35
Energy efficiency class:	C	DIMM DALI:	yes
Electrical protection class:	I	Number on the palette [pcs]:	40
Colour temperature [K]:	4000	Net weight [kg]:	1.409
Color rendering index (Ra) >:	80	UGR (4H8H):	<19
SDCM:	3	Category of application:	office lighting
LED lifespan L70B50 [h]:	153000	Warranty [years]:	5
LED lifespan L80B10 [h]:	96000	CE certificate:	<a href="#">122/2025</a>
LED lifespan L90B10 [h]:	46000	Manual:	<a href="#">Download PDF</a>
Beam angle [°]:	60	Environmental Product Declaration (EPD):	<a href="#">852/2025</a>
Optics:	lens	Plik LDT:	<a href="#">Download</a>
Optics material:	PC		

Card creation date: 01 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 122/2025