

BARIS 40 LED UGR PLUS N 5625LM DALI I CL. IP20 1421MM 830 45W WHITE 60D

DETAILED CARD



TECHNICAL PARAMETERS

Index:	769436
Ingress protection:	IP20
Impact resistance:	IK03
Rated power of the luminaire [W]*:	45
Luminous flux [lm]*:	5625
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	white

CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver. The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

BARIS 40 LED UGR PLUS N 5625LM DALI I CL. IP20 1421MM 830 45W WHITE 60D

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	769436	Optics material:	PC
EAN:	5905963769436	Material of the body:	aluminium
Light source:	LED	Colour of the body:	white
Rated power of the luminaire [W]:	45	Dimensions (H/W/T/S) [mm]:	53/40/1421
Luminous flux [lm]:	5625	Mounting dimensions [mm]:	1355
Supply voltage [V]:	220 - 240	Impact resistance:	IK03
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous efficacy [lm/W]:	125	Mounting version:	surface
Energy efficiency class:	D	Working temperature [°C]:	35
Electrical protection class:	I	DIMM DALI:	yes
Colour temperature [K]:	3000	Number on the palette [pcs]:	40
Colour rendering index:	>80	Net weight [kg]:	1.609
SDCM:	≤ 3	UGR (4H8H):	<19
LED lifespan L70B50 [h]:	153000	Warranty [years]:	5
LED lifespan L80B20 [h]:	96000	CE certificate:	102/2024
LED lifespan L90B10 [h]:	46000	Manual:	Download PDF
Beam angle [°]:	60	Plik LDT:	Download
Optics:	lens		