

BARIS 40 LED UGR PLUS Z 3325LM I CL. IP20 1140MM 840 27W ANODE CO 60D

DETAILED CARD



TECHNICAL PARAMETERS

Index:	769511
Ingress protection:	IP20
Impact resistance:	IK03
Rated power of the luminaire [W]*:	27
Luminous flux [lm]*:	3325
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	grey

CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver. The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

