

BARIS 40 LED UGR PLUS Z 3275LM I CL. IP20 1140MM 840 24W BLACK 60D

DETAILED CARD



TECHNICAL PARAMETERS

Index:	769535
Ingress protection:	IP20
Impact resistance:	IK03
Rated power of the luminaire [W]*:	24
Luminous flux [lm]*:	3275
Colour temperature [K]:	4000
Material of the body:	aluminium
Colour of the body:	black

CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver. The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

BARIS 40 LED UGR PLUS Z 3275LM I CL. IP20 1140MM 840 24W BLACK 60D

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	769535	Optics material:	PC
EAN:	5905963769535	Material of the body:	aluminium
Light source:	LED	Colour of the body:	black
Rated power of the luminaire [W]:	24	Dimensions (H/W/T/S) [mm]:	53/40/1140
Luminous flux [lm]:	3275	Mounting dimensions [mm]:	1030
Supply voltage [V]:	220 - 240	Impact resistance:	IK03
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous efficacy [lm/W]:	136	Mounting version:	suspended
Energy efficiency class:	D	Working temperature [°C]:	35
Electrical protection class:	I	Number on the palette [pcs]:	40
Colour temperature [K]:	4000	Net weight [kg]:	1.504
Color rendering index (Ra) >:	80	UGR (4H8H):	<19
SDCM:	3	Category of application:	office lighting
LED lifespan L70B50 [h]:	153000	Warranty [years]:	5
LED lifespan L80B10 [h]:	96000	CE certificate:	122/2025
LED lifespan L90B10 [h]:	46000	Manual:	Download PDF
Beam angle [°]:	60	Environmental Product Declaration (EPD):	852/2025
Optics:	lens	Plik LDT:	Download

Card creation date: 01 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 122/2025