

# BARIS 40 LED UGR PLUS Z 2925LM I CL. IP44 1140MM 830 27W ANODE CO 60D

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |             |
|------------------------------------|-------------|
| Index:                             | 771071      |
| Ingress protection:                | IP44        |
| Impact resistance:                 | IK03        |
| Rated power of the luminaire [W]*: | 27          |
| Luminous flux [lm]*:               | 2925        |
| Colour temperature [K]:            | 3000        |
| Material of the body:              | aluminium   |
| Colour of the body:                | grey        |
| Diffuser material:                 | PC          |
| Diffuser type:                     | transparent |

## CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver. The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

## APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

# BARIS 40 LED UGR PLUS Z 2925LM I CL. IP44 1140MM 830 27W ANODE CO 60D

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                              |                              |
|-----------------------------------|---------------|------------------------------|------------------------------|
| Index:                            | 771071        | Diffuser type:               | transparent                  |
| EAN:                              | 5905963771071 | Optics:                      | lens                         |
| Light source:                     | LED           | Optics material:             | PC                           |
| Rated power of the luminaire [W]: | 27            | Material of the body:        | aluminium                    |
| Luminous flux [lm]:               | 2925          | Colour of the body:          | grey                         |
| Supply voltage [V]:               | 220 - 240     | Dimensions (H/W/T/S) [mm]:   | 53/40/1140                   |
| Frequency [Hz]:                   | 50 - 60       | Mounting dimensions [mm]:    | 1030                         |
| Luminous efficacy [lm/W]:         | 108           | Impact resistance:           | IK03                         |
| Energy efficiency class:          | E             | Ingress protection:          | IP44                         |
| Electrical protection class:      | I             | Mounting version:            | suspended                    |
| Colour temperature [K]:           | 3000          | Working temperature [°C]:    | 35                           |
| Colour rendering index:           | 80            | Number on the palette [pcs]: | 40                           |
| SDCM:                             | ≤ 3           | Net weight [kg]:             | 1.869                        |
| LED lifespan L70B50 [h]:          | 153000        | UGR (4H8H):                  | <19                          |
| LED lifespan L80B20 [h]:          | 96000         | Warranty [years]:            | 5                            |
| LED lifespan L90B10 [h]:          | 46000         | CE certificate:              | <a href="#">102/2024</a>     |
| Beam angle [°]:                   | 60            | Manual:                      | <a href="#">Download PDF</a> |
| Diffuser material:                | PC            | Plik LDT:                    | <a href="#">Download</a>     |

Card creation date: 29 November 2024  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 102/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)