

# BARIS 40 LED UGR PLUS Z 4925LM I CL. IP44 1421MM 840 45W ANODE CO 60D

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	771194
<b>Ingress protection:</b>	IP44
<b>Impact resistance:</b>	IK03
<b>Rated power of the luminaire [W]*:</b>	45
<b>Luminous flux [lm]*:</b>	4925
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	aluminium
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	transparent

## CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver. The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

## APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.


# BARIS 40 LED UGR PLUS Z 4925LM I CL. IP44 1421MM 840 45W ANODE CO 60D

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	45	Diffuser type:	transparent
Index:	771194	Colour of the body:	grey
Colour temperature [K]:	4000	Optics:	lens
EAN:	5905963771194	Optics material:	PC
Luminous flux [lm]:	4925	Mounting version:	suspended
Light source:	LED	Material of the body:	aluminium
Beam angle [°]:	60	Dimensions (H/W/T/S) [mm]:	53/40/1421
Supply voltage [V]:	220 - 240	Mounting dimensions [mm]:	1310
Frequency [Hz]:	50 - 60	Impact resistance:	IK03
Luminous efficacy [lm/W]:	109	Working temperature [°C]:	35
Energy efficiency class:	E	Number on the palette [pcs]:	40
Electrical protection class:	I	Net weight [kg]:	2.174
Colour rendering index:	>80	UGR (4H8H):	<19
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	153000	CE certificate:	<a href="#">102/2024</a>
LED lifespan L80B20 [h]:	96000	Manual:	<a href="#">Download PDF</a>
LED lifespan L90B10 [h]:	46000	Plik LDT:	<a href="#">Download</a>
Diffuser material:	PC		
Ingress protection:	IP44		

## LIGHT CURVES



Card creation date: 29 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 102/2024



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)