

BARIS 40 LED UGR PLUS Z 4200LM DALI I CL. IP44 1421MM 830 35W WHITE 60D

DETAILED CARD



TECHNICAL PARAMETERS

Index:	771347
Ingress protection:	IP44
Impact resistance:	IK03
Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	4200
Colour temperature [K]:	3000
Material of the body:	aluminium
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	transparent

CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver. The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

BARIS 40 LED UGR PLUS Z 4200LM DALI I CL. IP44 1421MM 830 35W WHITE 60D

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	771347	Diffuser type:	transparent
EAN:	5905963771347	Optics:	lens
Light source:	LED	Optics material:	PC
Rated power of the luminaire [W]:	35	Material of the body:	aluminium
Luminous flux [lm]:	4200	Colour of the body:	white
Supply voltage [V]:	220 - 240	Dimensions (H/W/T/S) [mm]:	53/40/1421
Frequency [Hz]:	50 - 60	Mounting dimensions [mm]:	1310
Luminous efficacy [lm/W]:	120	Impact resistance:	IK03
Energy efficiency class:	D	Ingress protection:	IP44
Electrical protection class:	I	Mounting version:	suspended
Colour temperature [K]:	3000	Working temperature [°C]:	35
Colour rendering index:	>80	DIMM DALI:	yes
SDCM:	≤ 3	Number on the palette [pcs]:	40
LED lifespan L70B50 [h]:	153000	Net weight [kg]:	2.199
LED lifespan L80B20 [h]:	96000	UGR (4H8H):	<19
LED lifespan L90B10 [h]:	46000	Warranty [years]:	5
Beam angle [°]:	60	CE certificate:	102/2024
Diffuser material:	PC	Manual:	Download PDF

Card creation date: 29 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 102/2024