

BARIS 40 LED UGR PLUS Z 3575LM I CL. IP44 1421MM 840 35W BLACK 70D

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-------------|
| Index: | 771682 |
| Ingress protection: | IP44 |
| Impact resistance: | IK03 |
| Rated power of the luminaire [W]*: | 35 |
| Luminous flux [lm]*: | 3575 |
| Colour temperature [K]: | 4000 |
| Material of the body: | aluminium |
| Colour of the body: | black |
| Diffuser material: | PC |
| Diffuser type: | transparent |

CHARACTERISTICS

The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver. The luminaire is equipped with a unique suspension system that facilitates the installation of the lamp and adjustment of the suspension. All BARIS 40 LED suspended luminaires contain 1.2 m long suspensions with a box included in the set.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

BARIS 40 LED UGR PLUS Z 3575LM I CL. IP44 1421MM 840 35W BLACK 70D

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|------------------------------|------------------------------|
| Rated power of the luminaire [W]: | 35 | Ingress protection: | IP44 |
| Index: | 771682 | Diffuser type: | transparent |
| Colour temperature [K]: | 4000 | Colour of the body: | black |
| EAN: | 5905963771682 | Optics: | lens |
| Luminous flux [lm]: | 3575 | Optics material: | PC |
| Light source: | LED | Mounting version: | suspended |
| Beam angle [°]: | 70 | Material of the body: | aluminium |
| Supply voltage [V]: | 220 - 240 | Dimensions (H/W/T/S) [mm]: | 53/40/1421 |
| Frequency [Hz]: | 50 - 60 | Mounting dimensions [mm]: | 1310 |
| Luminous efficacy [lm/W]: | 102 | Impact resistance: | IK03 |
| Energy efficiency class: | E | Working temperature [°C]: | 35 |
| Electrical protection class: | I | Number on the palette [pcs]: | 40 |
| Colour rendering index: | >80 | Net weight [kg]: | 2.174 |
| SDCM: | ≤ 3 | UGR (4H8H): | <19 |
| LED lifespan L70B50 [h]: | 153000 | Warranty [years]: | 5 |
| LED lifespan L80B20 [h]: | 96000 | CE certificate: | 102/2024 |
| LED lifespan L90B10 [h]: | 46000 | Manual: | Download PDF |
| Diffuser material: | PC | | |

Card creation date: 29 November 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 102/2024