# ALTEZZO L 100 IOT BT HYT 1-10V 1200MM 700LM 840 AS IP65 RAL7016 6W (120)

**DETAILED CARD** 







### ALTEZZO L 100 IOT BT HYT 1-10V 1200MM 700LM 840 AS IP65 RAL7016 6W (120)

**DETAILED CARD** 

### **TECHNICAL PARAMETERS**

Index: 986871

Rated power of the luminaire [W]\*: 6

Luminous flux [lm]\*: 700

Colour temperature [K]: 3000

Luminous efficacy [lm/W]: 117

Energy efficiency class: D

Electrical protection class:

Color rendering index (Ra) >: 80

Beam angle [°]:

Light distribution type: asymmetric

### **CHARACTERISTICS**

Altezzo L 100 IoT is a family of outdoor lamps with a modern design. They are offered in four sizes - with heights ranging from 600 mm to 1500 mm. Their impact-resistant (IK08) and compact profile (100 mm x 40 mm) is made of aluminum in graphite color (RAL 7016). The light module consists of leds with a life span of up to 196,000 h, with lenses made of PMMA and a durable polycarbonate diffuser.IoT characteristicsThe IoT BT HYT 1-10V version has a built-inBT HYT module that allows you to program functions in the Lena Lighting Clue app and control in real time, and a 1-10V driver that allows you to dim the light source.

### **APPLICATION**

The wide range of luminous fluxes in the Altezzo L 100 lamp series allows to design energy-efficient lighting in the amount required by the norm, both in walking alleys and building surroundings. Versions with lower wattages will work well in parks and gardens for illuminating small architecture.

The lamps are designed for operation in low and high temperatures from -30°C to +50°C and in harsh weather conditions. They are characterized by a very high IP65 tightness.

### **DETAILS**

The selection of the foundation for the lighting column, in accordance with the Building Act, rests with the designer, with the relevant qualifications. The designer is also obliged to check the standard solution from the lighting manufacturer's offer, as he knows, among other things, the soil and water conditions in the designed area. If the dedicated foundation does not provide the safe conditions specified in the design, a suitable one should be selected from outside the lighting manufacturer's offer, with an anchor spacing of 180x180 - 220x220mm. As standard, in the case of **Altezzo L100**, universal 13kg foundations are used for garden lamps or FBO 35/7.5 M6 foundations for taller posts and/or more difficult ground and water conditions.



## ALTEZZO L 100 IOT BT HYT 1-10V 1200MM 700LM 840 AS IP65 RAL7016 6W (120)

**DETAILED CARD** 

### **TECHNICAL PARAMETERS TABLE**

	000074
Index:	986871
EAN:	5905963986871
Light source:	LED module
Rated power of the luminaire [W]:	6
Luminous flux [lm]:	700
Luminous flux of the luminaire 30min [lm]*:	700
Supply voltage [V]:	220-240
AC voltage range [V]:	90-264
Frequency [Hz]:	50-60
Luminous efficacy [lm/W]:	117
Energy efficiency class:	D
Electrical protection class:	1
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Beam angle [°]:	110
Light distribution type:	asymmetric
Surge protection [kV]:	2
Diffuser material:	PC
Optics:	lens

Optics material:	PMMA
Material of the body:	aluminium
Colour of the body:	RAL7016
Dimensions (H/W/T/S) [mm]:	235/140/1200
Mounting dimensions [mm]:	75x75 - 90x90
Impact resistance:	IK08
Ingress protection:	IP65
Mounting version:	on a foundation
Working temperature [°C]:	from -25 to +50
Corridor function:	yes
DIMM DALI:	yes
Control:	yes
Master/slave:	slave
Dimensions of single box [mm]:	1550/210/200
Number on the palette [pcs]:	18
Net weight [kg]:	4
Warranty [years]:	5
CE certificate:	93/2023
Manual:	Download PDF

Card creation date: 21 November 2024



