CONTRA PLUS LED 595X595MM MULTI 3200-4900LM 840/830 IP44/IP20 II CL. MAT PMMA 26-39W DALI

DETAILED CARD





TECHNICAL PARAMETERS

Index: 375699

Rated power [W] - range: 26-39

Luminous flux of the luminaire [lm] -

range:

Colour temperature [K] - range: 4000/3000

3200-4900

Ingress protection: IP44/IP20

Impact resistance: IK03

Color rendering index (Ra) >: 80

Energy efficiency class:

Material of the body: coated aluminium

Diffuser material: PMMA

CHARACTERISTICS

Contra Plus LED versatile LED panel characterised by its low, slim profile and elegant design. Adapted for flush-mounted installation in modular ceilings, surface-mounted or suspended using an additional frame (available as an accessory). Luminaire with integrated energy-saving LED module, made of white painted aluminium profile, equipped with structured multi-layer PMMA MAT or PRM shade for perfect light diffusion. MULTI version. Choose from 2 light colours (3000K and 4000K) and 8 brightness levels in one LED panel thanks to the built-in switch.

APPLICATION

The luminaire is intended for indoor use in office (offices, conference rooms) or representative use (hotels, restaurants); illumination of public facilities, including hospitals, educational facilities, offices, halls, garages, passageways, warehouses, shops, as well as in the food industry and food-related retail and service facilities. The unique design and excellent light performance enable CONTRA PLUS LED to be used as the main source of light, also for work that requires visual focus. The lamp is suitable for both new applications and the replacement of traditional T8 and T5 luminaires with energy-efficient LED solutions.



CONTRA PLUS LED 595X595MM MULTI 3200-4900LM 840/830 IP44/IP20 II CL. MAT PMMA 26-39W DALI

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index: 375699 EAN: 5905963375699 Light source: LED Rated power [W] - range: 26-39 Luminous flux of the luminaire [Im] - range: 3200-4900 Colour temperature [K] - range: 4000/3000 Supply voltage [V]: 220-240 Frequency [Hz]: 50-60	
Light source: Rated power [W] - range: Luminous flux of the luminaire [Im] - range: Colour temperature [K] - range: 4000/3000 Supply voltage [V]: 220-240	
Rated power [W] - range: 26-39 Luminous flux of the luminaire [Im] - range: 3200-4900 Colour temperature [K] - range: 4000/3000 Supply voltage [V]: 220-240	
Luminous flux of the luminaire [lm] - range: Colour temperature [K] - range: Supply voltage [V]: 220-240	
Colour temperature [K] - range: 4000/3000 Supply voltage [V]: 220-240	
Supply voltage [V]: 220-240	
Frequency [Hz]: 50-60	
Luminous efficacy [lm/W]: 123	
Energy efficiency class: D	
Electrical protection class:	
Color rendering index (Ra) >: 80	
Beam angle [°]: 110	
Surge protection [kV]:	
Diffuser material: PMMA	
Diffuser type: matt	
Diffuser colour: milky	
Optics material: PMMA	
Optics: lens	
Material of the body: coated aluminium	

Calary of the hadro	white
Colour of the body:	write
DIMM DALI:	yes
Dimensions (H/W/T/S) [mm]:	595/595/39
Impact resistance:	IK03
Ingress protection:	IP44/IP20
Mounting version:	podtynkowy, natynkowy z akcesorium, zwieszany z akcesorium
Working temperature [°C]:	from 0 to +35
Dimensions of single box [mm]:	636
Number on the palette [pcs]:	50
Net weight [kg]:	1.200
Category type:	troffers
LED lifespan L70B50 [h]:	228000
LED lifespan L80B20 [h]:	143000
LED lifespan L90B10 [h]:	68000
Light distribution type:	lambertian
Additional accessories:	ramka natynkowa, system zwieszania
Warranty [years]:	5
CE certificate:	105/2024
Manual:	Download PDF
Plik LDT:	Download




CONTRA PLUS LED 595X595MM MULTI 3200-4900LM 840/830 IP44/IP20 II CL. MAT PMMA 26-39W DALI


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)
374715	CONTRA LED surface-mounted frame CLICK 600x600x65mm
374708	CONTRA LED surface-mounted frame CLICK 1200x300x65mm
374692	CONTRA LED suspension system 1200x300
374685	CONTRA LED suspension system 600x600
374838	CONTRA LED MOUNTING CLIPS IN KG (4PCS)
374845	Frame adapter KG 635x635 WHITE
374852	Frame adapter KG 1235x335 WHITE
998966	Frame steel white structure RAL9016 600x600 SM "well effect"
374722	CONTRA LED suspension system 600x600 DALI
374739	CONTRA LED - suspension system 1200x300 DALI



Plasterboard recessing kit 630x630 white (steel version) (999543)




CONTRA LED surface-mounted frame CLICK 600x600x65mm (374715)



CONTRA LED surface-mounted frame CLICK 1200x300x65mm (374708)



CONTRA LED suspension system 1200x300 (374692)



Frame steel white structure RAL9016 600x600 SM "well effect" (998966)

Card creation date: 18 July 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

