RQ 160 LED N 2050LM 830 IP44 I CL. PRM (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	573941
Ingress protection:	IP44
Nominal power [W]:	17
Luminous flux [lm]*:	2100
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Energy efficiency class:	E
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC

CHARACTERISTICS

RQ 160 LED N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.

RQ 160 LED N 2050LM 830 IP44 I CL. PRM (17W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	573941
EAN:	5905963573941
Nominal power [W]:	17
Rated power of the luminaire [W]:	18
Supply voltage [V]:	220-240
Frequency [Hz]:	50-60
Luminous flux [lm]:	2100
Luminous efficacy [lm/W]:	112
Energy efficiency class:	E
Electrical protection class:	I
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.99
Beam angle [°]:	115
Diffuser material:	PC
Diffuser type:	PRM
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	171/97

Mounting dimensions [mm]:	80
Impact resistance:	IK08
Ingress protection:	IP44
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Number on the palette [pcs]:	120
Net weight [kg]:	0.720
LED lifespan L70B50 [h]:	150000
LED lifespan L80B10 [h]:	100000
LED lifespan L90B10 [h]:	50000
Light distribution type:	lambertian
Category of application:	educational institutions, HoReCa, commercial facilities
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	29/2025
PZH certificate:	B-BK-60112-0365-2022
Environmental Product Declaration (EPD):	944/2026
Manual:	Download PDF
ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018
Plik LDT:	Download

LIGHT CURVES



RQ 160 LED N 2050LM 830 IP44 I CL. PRM (17W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date: 10 December 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 29/2025

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl