

# RQ 160 LED N 2200LM 840 IP44 I CL. PRM (17W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	573958
<b>Ingress protection:</b>	IP44
<b>Nominal power [W]:</b>	17
<b>Luminous flux [lm]*:</b>	2200
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	>80
<b>Energy efficiency class:</b>	D
<b>Material of the body:</b>	ABS
<b>Colour of the body:</b>	white
<b>Diffuser material:</b>	PC

## CHARACTERISTICS

RQ 160 LED N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.


# RQ 160 LED N 2200LM 840 IP44 I CL. PRM (17W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	17	Material of the body:	ABS
Index:	573958	Colour of the body:	white
Colour temperature [K]:	4000	Mounting dimensions [mm]:	80
EAN:	5905963573958	Impact resistance:	IK08
Luminous flux [lm]:	2200	Mounting version:	surface
Diffuser type:	PRM	Working temperature [°C]:	from -20 to +35
Ingress protection:	IP44	Number on the palette [pcs]:	120
Rated power of the luminaire [W]:	18	Net weight [kg]:	0.720
Dimensions (H/W/T/S) [mm]:	171/97	LED lifespan L70B50 [h]:	132000
Supply voltage [V]:	220-240	LED lifespan L80B20 [h]:	84000
Frequency [Hz]:	50-60	LED lifespan L90B10 [h]:	42000
Luminous efficacy [lm/W]:	122	Light distribution type:	lambertian
Energy efficiency class:	D	Category of application:	HoReCa, commercial facilities, educational institutions, art and culture
Electrical protection class:	I	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	<a href="#">317/2023</a>
Power factor:	0.99	PZH certificate:	
Beam angle [°]:	115	Manual:	<a href="#">Download PDF</a>
Diffuser material:	PC	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# RQ 160 LED N 2200LM 840 IP44 I CL. PRM (17W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date: 10 December 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 317/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl