

RQ 160 LED PLUS N 2200LM 840 IP44 II CL. PRM (17W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|--------|
| Index: | 574931 |
| Ingress protection: | IP44 |
| Impact resistance: | IK08 |
| Nominal power [W]: | 17 |
| Luminous flux [lm]*: | 2200 |
| Colour temperature [K]: | 4000 |
| Color rendering index (Ra) >: | 80 |
| SDCM: | 3 |
| Electrical protection class: | II |
| Energy efficiency class: | D |

CHARACTERISTICS

RQ 160 LED PLUS N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.


RQ 160 LED PLUS N 2200LM 840 IP44 II CL. PRM (17W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|------------------------------|--|
| Index: | 574931 | Dimensions (H/W/T/S) [mm]: | 171/97 |
| EAN: | 5905963574931 | Mounting dimensions [mm]: | 80 |
| Nominal power [W]: | 17 | Impact resistance: | IK08 |
| Rated power of the luminaire [W]: | 18 | Ingress protection: | IP44 |
| Supply voltage [V]: | 220-240 | Mounting version: | surface |
| Frequency [Hz]: | 50-60 | Working temperature [°C]: | from -20 to +35 |
| Luminous flux [lm]: | 2200 | Number on the palette [pcs]: | 120 |
| Luminous efficacy [lm/W]: | 122 | Net weight [kg]: | 0.720 |
| Energy efficiency class: | D | Category type: | downlights |
| Electrical protection class: | II | LED lifespan L70B50 [h]: | 150000 |
| Colour temperature [K]: | 4000 | LED lifespan L80B10 [h]: | 100000 |
| Color rendering index (Ra) >: | 80 | LED lifespan L90B10 [h]: | 50000 |
| SDCM: | 3 | Light distribution type: | lambertian |
| Power factor: | 0.99 | Photobiological safety: | RG0 - exempt (no photobiological hazard) |
| Beam angle [°]: | 115 | Warranty [years]: | 5 |
| Diffuser material: | PC | CE certificate: | 28/2025 |
| Diffuser type: | PRM | PZH certificate: | B-BK-60112-0365/2022 |
| Material of the body: | ABS | Manual: | Download PDF |
| Colour of the body: | white | Plik LDT: | Download |

LIGHT CURVES



RQ 160 LED PLUS N 2200LM 840 IP44 II CL. PRM (17W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|---|
| 573637 | Suspension RQ160 fi100 white ON/OFF. DALI |

Card creation date: 10 December 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 28/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl