


MESSAGGIO 1261MM 3650LM 840 IP20 I CL. DALI 57W

RAL9016/RAL2004

DETAILED CARD



TECHNICAL PARAMETERS

Index:	579448
Light source:	LED
Rated power [W] - range:	57
Luminous flux of the luminaire [lm] - range:	3650
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Electrical protection class:	I
Colour temperature [K]:	4000
Ingress protection:	IP20
Diffuser material:	PC

CHARACTERISTICS

The MESSAGGIO collection, designed by Dorota Koziara, includes pendant lamps with a minimalist form. They can come in all RAL colors, including a multicolor version, where the outside of the housing and the inside of the lamp have different colors. In this way, MESSAGGIO provides unlimited design possibilities.

Thanks to the possibility of adjusting the length of the pendants from the MESSAGGIO lamps, surprising light compositions can be created. Versions with DALI control allow you to change the value of the light output, which further enhances the decorative effect. The milky lampshade is made of PC, while the housing is made of solid yet visually delicate steel, which ensures the durability of the product.

APPLICATION

MESSAGGIO is a collection within which it is possible to create multicolor variants of lamps. In addition, the juxtaposition of their different versions - pendant, wall sconces and standing - allows you to create phenomenal light-decorative compositions, which will work well in places such as hotels, restaurants, art galleries, shopping malls, representative spaces, as well as private homes.

MESSAGGIO 1261MM 3650LM 840 IP20 I CL. DALI 57W

RAL9016/RAL2004

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	579448
Rated power [W] - range:	57
EAN:	5905963579448
Luminous flux of the luminaire [lm] - range:	3650
Light source:	LED
Rated power of the luminaire [W]:	57
Luminous flux [lm]:	3650
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Colour temperature [K]:	4000
Luminous efficacy [lm/W]:	64
Electrical protection class:	I
SDCM:	≤ 3
LED lifespan L70B50 [h]:	99000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	31000
Beam angle [°]:	116x58
Light distribution type:	open space
Diffuser material:	PC

Diffuser type:	OPAL
Colour of the body:	RAL9016/2004
Diffuser colour:	milky
Material of the body:	Steel
Dimensions (H/W/T/S) [mm]:	1230/1261/80
Mounting dimensions [mm]:	340
Ingress protection:	IP20
Mounting version:	suspended
Working temperature [°C]:	from -25 to +35
DIMM DALI:	yes
Diode PCB material:	aluminium
Control:	1
Net weight [kg]:	4
Warranty [years]:	5
Category type:	architectural
CE certificate:	207/2023
Manual:	Download PDF
Plik LDT:	Download