


# FACTOR LED 2M 71800LM 840 30D IP66 IK09 (562W) CMP

## DETAILED CARD



### TECHNICAL PARAMETERS

Index:	684289
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	562
Luminous flux [lm]*:	71800
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	D

### CHARACTERISTICS

Factor Led is a latest-generation floodlight with a high power output and an impressive luminous flux. It is characterized not only by very high luminous efficiency but also by the highest IP 66 tightness and IK09 impact resistance. These parameters have been achieved thanks to the branded components used, robust housing made of cast aluminum, and the use of a passive cooling system for the lamp, which allows the excess heat generated to be dissipated during lamp operation. The Factor Led has the advantage of very fast and easy installation. The lightweight steel arm is attached to the supporting structure (wall, pole), and then the light modules are plugged in. On a single bracket, the installer can plug in a lamp containing from 1 to 4 such modules.

### APPLICATION

Very good sealing and impact resistance parameters, the ability to work in elevated temperatures - up to 45 ° C as standard, and an extensive range of spreads predisposes Factor Led lamps to work in harsh weather conditions. It will find application and perform well both inside industrial halls, warehouses, sports halls, logistics centers, and outdoors - on sports fields, airports, parking lots, and maneuvering areas. It can also illuminate the facades of buildings and elements of external architecture.


**FACTOR LED 2M 71800LM 840 30D IP66 IK09 (562W) CMP**

### DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	684289	<b>Diffuser material:</b>	PC
<b>EAN:</b>	5905963684289	<b>Material of the body:</b>	aluminium
<b>Rated power of the luminaire [W]:</b>	562	<b>Colour of the body:</b>	RAL7016
<b>Luminous flux [lm]:</b>	71800	<b>Dimensions (H/W/T/S) [mm]:</b>	385/425/340
<b>Supply voltage [V]:</b>	220 - 240	<b>Impact resistance:</b>	IK09
<b>Frequency [Hz]:</b>	47 - 63	<b>Ingress protection:</b>	IP66
<b>Luminous efficacy [lm/W]:</b>	128	<b>Working temperature [°C]:</b>	od -40 do +30
<b>Energy efficiency class:</b>	D	<b>Accessories included:</b>	Metal peszel
<b>Electrical protection class:</b>	I	<b>Dimensions of single box [mm]:</b>	430/410/175
<b>Colour temperature [K]:</b>	4000	<b>Number on the palette [pcs]:</b>	18
<b>Colour rendering index:</b>	80	<b>Net weight [kg]:</b>	12.900
<b>SDCM:</b>	≤ 3	<b>Version:</b>	2 modules
<b>Power factor:</b>	0.98	<b>Warranty [years]:</b>	5
<b>LED lifespan L70B50 [h]:</b>	156000	<b>CE certificate:</b>	<a href="#">262/2023</a>
<b>LED lifespan L80B20 [h]:</b>	98000	<b>ENEC Certificate:</b>	<a href="#">0404/ENEC/25</a>
<b>LED lifespan L90B10 [h]:</b>	47000	<b>Environmental Product Declaration (EPD):</b>	<a href="#">816/2025</a>
<b>Beam angle [°]:</b>	30	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Surge protection [kV]:</b>	6		

## LIGHT CURVES




# FACTOR LED 2M 71800LM 840 30D IP66 IK09 (562W) CMP


DETAILED CARD

## ACCESSORIES AVAILABLE


index	Name
684791	Protective grid Factor LED 4M RAL7016
684784	Protective grid Factor LED 3M RAL7016
684777	Protective grid Factor LED 2M RAL7016
684760	Protective grid Factor LED 1M RAL7016



Protective grid Factor LED 4M  
RAL7016 (684791)



Protective grid Factor LED 3M  
RAL7016 (684784)



Protective grid Factor LED 2M  
RAL7016 (684777)

Card creation date: 21 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 262/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl