

FACTOR LED 3M 107700LM 840 30D IP66 IK09 (843W) CMP

DETAILED CARD



TECHNICAL PARAMETERS

Index:	684296
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	843
Luminous flux [lm]*:	107700
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

Factor Led is a latest-generation floodlight with a high power output and an impressive luminous flux. It is characterized not only by very high luminous efficiency but also by the highest IP 66 tightness and IK09 impact resistance. These parameters have been achieved thanks to the branded components used, robust housing made of cast aluminum, and the use of a passive cooling system for the lamp, which allows the excess heat generated to be dissipated during lamp operation. The Factor Led has the advantage of very fast and easy installation. The lightweight steel arm is attached to the supporting structure (wall, pole), and then the light modules are plugged in. On a single bracket, the installer can plug in a lamp containing from 1 to 4 such modules.

APPLICATION

Very good sealing and impact resistance parameters, the ability to work in elevated temperatures - up to 45 ° C as standard, and an extensive range of spreads predisposes Factor Led lamps to work in harsh weather conditions. It will find application and perform well both inside industrial halls, warehouses, sports halls, logistics centers, and outdoors - on sports fields, airports, parking lots, and maneuvering areas. It can also illuminate the facades of buildings and elements of external architecture.


FACTOR LED 3M 107700LM 840 30D IP66 IK09 (843W) CMP

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	684296	Diffuser material:	PC
EAN:	5905963684296	Material of the body:	aluminium
Rated power of the luminaire [W]:	843	Colour of the body:	RAL7016
Luminous flux [lm]:	107700	Dimensions (H/W/T/S) [mm]:	580/425/340
Supply voltage [V]:	220 - 240	Impact resistance:	IK09
Frequency [Hz]:	47 - 63	Ingress protection:	IP66
Luminous efficacy [lm/W]:	128	Working temperature [°C]:	od -40 do +30
Energy efficiency class:	D	Accessories included:	Metal peszel
Electrical protection class:	I	Dimensions of single box [mm]:	430/810/175
Colour temperature [K]:	4000	Number on the palette [pcs]:	18
Colour rendering index:	80	Net weight [kg]:	16.980
SDCM:	≤ 3	Version:	3 modules
Power factor:	0.98	Warranty [years]:	5
LED lifespan L70B50 [h]:	156000	CE certificate:	262/2023
LED lifespan L80B20 [h]:	98000	ENEC Certificate:	0404/ENEC/25
LED lifespan L90B10 [h]:	47000	Environmental Product Declaration (EPD):	816/2025
Beam angle [°]:	30	Manual:	Download PDF
Surge protection [kV]:	6		

LIGHT CURVES




FACTOR LED 3M 107700LM 840 30D IP66 IK09 (843W) CMP


DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
684791	Protective grid Factor LED 4M RAL7016
684784	Protective grid Factor LED 3M RAL7016
684777	Protective grid Factor LED 2M RAL7016
684760	Protective grid Factor LED 1M RAL7016



Protective grid Factor LED 4M
RAL7016 (684791)



Protective grid Factor LED 3M
RAL7016 (684784)



Protective grid Factor LED 2M
RAL7016 (684777)