

# TIARA 2 LED XS 6750LM 740 RM7 IP66 II CL. DALI (47W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	694363
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	47
<b>Luminous flux [lm]*:</b>	6750
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	70
<b>Electrical protection class:</b>	II
<b>Optics:</b>	RM7
<b>Control:</b>	Yes + 5-stage power reduction

## CHARACTERISTICS

TIARA 2 LED XS - a new generation of LED road luminaires. It uses directional multi-lens matrices made of PMMA, each lens of which has the same optics, ensuring that the light characteristics remain unchanged over time. The two-chamber structure of the luminaire maintains the tightness of the optical chamber during assembly work and when opening the electrical chamber. As standard, the fixture offers tool-free access to the electrical equipment using a knob which, upon request and the need to protect against vandalism or uncontrolled opening, can optionally be permanently secured with a screw or seal. The upper part of the luminaire has dedicated hinges and a rope protecting against falling. Using standard tools, quick and convenient service is possible, allowing the replacement of any component without the need to dismantle the entire fixture and perform soldered connections. The body and handle are made of die-cast aluminum, powder-coated gray, characterized by a very high degree of tightness IP66 and resistance to mechanical impacts IK10. Standard equipment: ergonomic light module suspension system; protection against accidental overheating of the NTC fixture; fully programmable DALI driver, available functions of maintaining a constant light flux during CLO and autonomous, 5-step power reduction; filter preventing water vapor condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; cooperation with control systems, RCR motion sensor; anti-vandal protection with screws/seals; additional SP10kV protection apart from the power supply, on/off power supply without power reduction function; knife switch disconnecting the voltage when the electrical compartment is opened; version with a cable terminated with a quick connector; painting in any color from the RAL palette. Certificates: CE, RoHS, ENEC, ENEC+, Zhaga D4i. Zhaga Book 13, Zhaga Book 15.

## APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate facilities such as: expressways, national roads, provincial roads, district roads, municipal roads, city roads, housing estate roads, and area lighting. Optics are also available to illuminate pedestrian crossings, sidewalks and bicycle paths.

# TIARA 2 LED XS 6750LM 740 RM7 IP66 II CL. DALI (47W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	694363	<b>Colour of the body:</b>	grey
<b>EAN:</b>	5905963694363	<b>Dimensions (H/W/T/S) [mm]:</b>	424/170/105
<b>ETIM class:</b>	EC000062	<b>Mounting dimensions [mm]:</b>	ø40-60
<b>Category type:</b>	street lighting	<b>Impact resistance:</b>	IK10
<b>Version:</b>	XS	<b>Ingress protection:</b>	IP66
<b>Light source:</b>	LED module	<b>Mounting version:</b>	Top, on pole / Side, on boom
<b>Rated power of the luminaire [W]:</b>	47	<b>Tilt angle adjustment [°]:</b>	-30 to +120 (peak); -120 to +30 (side)
<b>Supply voltage [V]:</b>	220 - 240	<b>Lateral surface (SCx) [m2]:</b>	0.021
<b>Frequency [Hz]:</b>	50 - 60	<b>Working temperature [°C]:</b>	from -40 to +50
<b>Luminous flux [lm]:</b>	6750	<b>DIMM DALI:</b>	yes
<b>Luminous efficacy [lm/W]:</b>	144	<b>Control:</b>	Yes + 5-stage power reduction
<b>Energy efficiency class:</b>	C	<b>Protection type:</b>	NTC + ESD
<b>Electrical protection class:</b>	II	<b>Vandalproof:</b>	yes
<b>Colour temperature [K]:</b>	4000	<b>Net weight [kg]:</b>	3.520
<b>Color rendering index (Ra) &gt;:</b>	70	<b>ULOR:</b>	0%
<b>SDCM:</b>	4	<b>Photobiological safety:</b>	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
<b>Power factor:</b>	0.96	<b>Technical Warranty:</b>	5 with the possibility of extension to 10
<b>Surge protection [kV]:</b>	10	<b>ENEC Certificate:</b>	<a href="#">0449/ENEC/25; 0163/ENEC+25</a>
<b>Diffuser material:</b>	tempered glass	<b>CE certificate:</b>	<a href="#">43/2024</a>
<b>Diffuser type:</b>	transparent	<b>Zhaga-D4i:</b>	<a href="#">ZG430708072024</a>
<b>Optics material:</b>	PMMA	<b>Environmental Product Declaration (EPD):</b>	<a href="#">682/2024</a>
<b>Optics:</b>	RM7	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Exchangeable source:</b>	yes	<b>LED lifespan L95B10 [h]:</b>	100000
<b>Material of the body:</b>	powder coated aluminium	<b>Category of application:</b>	Street lighting

## LIGHT CURVES



# TIARA 2 LED XS 6750LM 740 RM7 IP66 II CL. DALI (47W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
813474	Backshield P (right) Tiara 2 LED XS RAL9006
813481	Backshield L (left) Tiara 2 LED XS RAL9006
813467	Backshield T (back) Tiara 2 LED XS RAL9006
804625	TIARA 2 LED Adjustable bracket Dark Sky diameter 64 mm grey
989766	Tiara 2 LED 64mm handle cover



TIARA 2 LED Adjustable bracket Dark Sky diameter 64 mm grey (804625)



Tiara 2 LED 64mm handle cover (989766)

Card creation date: 26 March 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 43/2024