

# BARIS STAND 10150LM TUNABLE WHITE 2700-6500K IP20 II KL. BLACK 70D/120D H 81W

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	744808
Rated power of the luminaire [W]*:	81
Colour temperature [K] - range:	2700-6500
Luminous flux [lm]*:	10150
Colour rendering index:	>90
SDCM:	≤ 3
UGR (4H8H):	<10
Material of the body:	aluminium
Dimensions (H/W/T/S) [mm]:	2108
Mounting version:	Stojąca

## CHARACTERISTICS

## APPLICATION

# BARIS STAND 10150LM TUNABLE WHITE 2700-6500K IP20 II KL. BLACK 70D/120D H 81W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	744808	<b>Optics:</b>	lens
<b>EAN:</b>	5905963744808	<b>Optics material:</b>	PC
<b>Category type:</b>	architectural	<b>Material of the body:</b>	aluminium
<b>Light source:</b>	LED	<b>Dimensions (H/W/T/S) [mm]:</b>	2108
<b>Rated power of the luminaire [W]:</b>	81	<b>Impact resistance:</b>	IK03
<b>Colour temperature [K] - range:</b>	2700-6500	<b>Ingress protection:</b>	IP20
<b>Luminous flux [lm]:</b>	10150	<b>Mounting version:</b>	Stojąca
<b>Colour of the body:</b>	black	<b>Working temperature [°C]:</b>	35
<b>Supply voltage [V]:</b>	220 - 240	<b>PIR:</b>	yes
<b>Frequency [Hz]:</b>	50-60	<b>Socket type:</b>	USB
<b>Luminous efficacy [lm/W]:</b>	125	<b>Dusk sensor:</b>	yes
<b>Energy efficiency class:</b>	D	<b>Sockets:</b>	3
<b>Electrical protection class:</b>	II	<b>Control:</b>	Inne
<b>Colour rendering index:</b>	>90	<b>Switch:</b>	yes
<b>SDCM:</b>	≤ 3	<b>Cable length [m]:</b>	3
<b>UGR (4H8H):</b>	<10	<b>Dimensions of single box [mm]:</b>	2183
<b>LED lifespan L70B50 [h]:</b>	142000	<b>Dimensions of bulk box (H/W/D) [mm]:</b>	brak
<b>LED lifespan L80B20 [h]:</b>	89000	<b>Number on the palette [pcs]:</b>	12
<b>LED lifespan L90B10 [h]:</b>	42500	<b>Warranty [years]:</b>	2
<b>Beam angle [°]:</b>	70/120	<b>CE certificate:</b>	<a href="#">01/2025</a>
<b>Light distribution type:</b>	symmetric	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Surge protection [kV]:</b>	2		

Card creation date: 03 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 01/2025