


FACTOR LED 1M 19900 LM 840 RW10 IP66 (122W)SH

DETAILED CARD



TECHNICAL PARAMETERS

Index:	994678
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	122
Luminous flux [lm]*:	19900
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 5
Electrical protection class:	I
Energy efficiency class:	B

CHARACTERISTICS

Factor Led is a latest-generation floodlight with a high power output and an impressive luminous flux. It is characterized not only by very high luminous efficiency but also by the highest IP 66 tightness and IK09 impact resistance. These parameters have been achieved thanks to the branded components used, robust housing made of cast aluminum, and the use of a passive cooling system for the lamp, which allows the excess heat generated to be dissipated during lamp operation. The Factor Led has the advantage of very fast and easy installation. The lightweight steel arm is attached to the supporting structure (wall, pole), and then the light modules are plugged in. On a single bracket, the installer can plug in a lamp containing from 1 to 4 such modules.

APPLICATION

Very good sealing and impact resistance parameters, the ability to work in elevated temperatures - up to 45 ° C as standard, and an extensive range of spreads predisposes Factor Led lamps to work in harsh weather conditions. It will find application and perform well both inside industrial halls, warehouses, sports halls, logistics centers, and outdoors - on sports fields, airports, parking lots, and maneuvering areas. It can also illuminate the facades of buildings and elements of external architecture.


FACTOR LED 1M 19900 LM 840 RW10 IP66 (122W)SH

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	122	Surge protection [kV]:	6
Index:	994678	Material of the body:	aluminium
Luminous flux [lm]:	19900	Colour of the body:	RAL7016
Beam angle [°]:	RW10	Dimensions (H/W/T/S) [mm]:	191/425/217
Diffuser material:	tempered glass	Impact resistance:	IK09
Supply voltage [V]:	220-240	Ingress protection:	IP66
Frequency [Hz]:	47-63	Working temperature [°C]:	from -40 to +45
Luminous efficacy [lm/W]:	163	Dimensions of single box [mm]:	430
Energy efficiency class:	B	Number on the palette [pcs]:	35
Electrical protection class:	I	Net weight [kg]:	5,590
Colour temperature [K]:	4000	Warranty [years]:	5
Colour rendering index:	>80	CE certificate:	262/2023
SDCM:	≤ 5	ENEC Certificate:	
Power factor:	0.98	Manual:	Download PDF
DIMM 1-10V:	yes	Plik LDT:	Download
Version:	1 module		

LIGHT CURVES



FACTOR LED 1M 1990 LM 840 RW10 IP66 (122W)SH

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
684791	Protective grid Factor LED 4M RAL7016
684784	Protective grid Factor LED 3M RAL7016
684777	Protective grid Factor LED 2M RAL7016
684760	Protective grid Factor LED 1M RAL7016



Protective grid Factor LED 4M
RAL7016 (684791)



Protective grid Factor LED 3M
RAL7016 (684784)



Protective grid Factor LED 2M
RAL7016 (684777)

Card creation date: 21 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 262/2023