

# SMART LED EVO NT AS 1161MM 3200LM IKL ANODA CO IP20 840 (50W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	378256
Nominal power [W]:	50
Luminous flux [lm]*:	3200
Colour temperature [K]:	4000
SDCM:	≤ 3
Energy efficiency class:	G
Material of the body:	aluminium
Diffuser material:	PMMA
Diffuser type:	OPAL
Mounting version:	surface

## CHARACTERISTICS

Surface or recessed very narrow luminaire including an integrated, energy-saving LED GO! light source. Body made from grey anodized aluminium. The optical system: asymmetric.

## APPLICATION

Particularly well suited for indoor use. The fixture is perfect for illumination of boards, paintings and display cases. The fixture is applied mostly in schools, universities, museums and art galleries.

# SMART LED EVO NT AS 1161MM 3200LM IKL ANODA CO IP20 840 (50W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Light source:	LED module	Colour of the body:	C0 anode
Nominal power [W]:	50	Dimensions (H/W/T/S) [mm]:	55/70/1165
Rated power of the luminaire [W]:	53.50	Impact resistance:	IK06
Supply voltage [V]:	220-240	Ingress protection:	IP20
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	3200	Net weight [kg]:	2.690
Luminous efficacy [lm/W]:	59	CE certificate:	<a href="#">114/2018</a>
Energy efficiency class:	G	Index:	378256
Electrical protection class:	I	EAN:	5905963378256
Colour temperature [K]:	4000	Category type:	battens
Colour rendering index:	>80	Light distribution type:	asymmetric
SDCM:	≤ 3	ETIM class:	EC000109
Power factor:	0.98	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	PMMA	Warranty [years]:	5
Diffuser type:	OPAL	Manual:	<a href="#">Download PDF</a>
Material of the body:	aluminium		

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 114/2018



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)