

# MERCURY LED RCR 8W PC OPAL IP54 3000K

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	187209/PA
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	8
Luminous flux [lm]*:	700
Colour temperature [K]:	3000
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	PP
Diffuser material:	PC

## CHARACTERISTICS

Surface mounted, round LED light fixture with a high luminous flux (94 lm/W), high ingress protection class IP54 and an integrated energy-saving light source LED GO!. Base and ring made of UV-resistant plastic. Specially formed diffuser made of impact resistant PC ensures the highest impact resistance of the fitting (IK10). Available in white; optional equipment: radio motion sensor (RCR). Color temperature 3000K/4000K, CRI>80, lifespan of LED 50 000h (L70B50) ta= 25 °C.

## APPLICATION

Luminaire suited for surface mounting on ceilings or walls, intended for outdoor (façade lighting) or indoor use (rooms with high humidity, passageways). Available option with a radio motion sensor (RCR) – particularly well suited for passageways and usable rooms.

### DETAILED CARD

<b>Light source:</b>	LED module
<b>Nominal power [W]:</b>	8
<b>Rated power of the luminaire [W]:</b>	9
<b>Supply voltage [V]:</b>	220-240
<b>Frequency [Hz]:</b>	50 - 60
<b>Luminous flux [lm]:</b>	700
<b>Luminous efficacy [lm/W]:</b>	78
<b>Energy efficiency class:</b>	F
<b>Electrical protection class:</b>	I
<b>Colour temperature [K]:</b>	3000
<b>Colour rendering index:</b>	80
<b>SDCM:</b>	≤ 3
<b>Power factor:</b>	0.53
<b>LED lifespan L70B50 [h]:</b>	50000
<b>Beam angle [°]:</b>	120
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	OPAL

Material of the body:	PP
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	ø255/85
Impact resistance:	IK10
Ingress protection:	IP54
Mounting version:	surface
Working temperature [°C]:	from -20 to +35
Motion sensor:	yes
Net weight [kg]:	0.620
Warranty [years]:	5
CE certificate:	<a href="#">399/2023</a>
Index:	187209/PA
EAN:	5905963187209
Category type:	bulkheads
ETIM class:	EC002892
Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Manual:	<a href="#">Download PDF</a>

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

