

SKVER S Z1 3450LM 740 RM7 MF IP66 II CL. DALI B 0 (23W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|-------------------------------|
| Index: | 802249 |
| Ingress protection: | IP66 |
| Impact resistance: | IK10 |
| Rated power of the luminaire [W]*: | 23 |
| Luminous flux [lm]*: | 3450 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 70 |
| Electrical protection class: | II |
| Optics: | RM7 |
| Control: | Yes + 5-stage power reduction |

CHARACTERISTICS

Skver LED S (Z1 MF) modular, equipped with an adjustable bracket, innovative park and city LED luminaire with tool-free access to the equipment compartment, equipped with a tool-free service plate compliant with the ZhagaBook 13 and 15 standard, adapted for both top and boom mounting. Made of pressure-formed aluminum, equipped with a flat glass shade, characterized by ULR = 0, maximum resistance to mechanical impact and increased color rendering index. The luminaire is available in variants with omnidirectional and directed lighting. The luminaire allows the use of dedicated functional accessories in the form of a screen that limits disturbing glare.

APPLICATION

Skver LED S (Z1 MF) is ideal for biologically active spaces, where the protection of the dark sky plays a special role, such as parks, squares, urban green islands, urban interiors in accordance with the photometric project, pedestrian routes, residential roads, parking lots and gardens. The luminaire is also suitable for lighting streets and roads of class M4 and M5. Thanks to the ULR = 0 index, it protects the urban ecosystem from excessive light emission into the upper half-space, restoring the dark night sky over cities.


SKVER S Z1 3450LM 740 RM7 MF IP66 II CL. DALI B 0 (23W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|--|------------------------|---|--|
| Index: | 802249 | Material of the body: | powder coated aluminium |
| EAN: | 5905963802249 | Colour of the body: | black |
| Category type: | Park and city lighting | Dimensions (H/W/T/S) [mm]: | 461/360/188 |
| Version: | S | Mounting dimensions [mm]: | ø60 |
| Light source: | LED module | Impact resistance: | IK10 |
| Rated power of the luminaire [W]: | 23 | Ingress protection: | IP66 |
| Supply voltage [V]: | 220-240 | Mounting version: | Top, on pole / Side, on boom |
| Frequency [Hz]: | 47-63 | Working temperature [°C]: | from -40 to +50 |
| Luminous flux [lm]: | 3450 | DIMM DALI: | yes |
| Luminous efficacy [lm/W]: | 156 | Control: | Yes + 5-stage power reduction |
| Energy efficiency class: | C | Protection type: | NTC |
| Electrical protection class: | II | Net weight [kg]: | 6 |
| Colour temperature [K]: | 4000 | Wire type: | HO7 RNF-2x1 |
| Colour rendering index: | 70 | LED lifespan L95B10 [h]: | 100000 |
| Power factor: | 0.96 | Photobiological safety: | RG0 - exempt (no photobiological hazard) |
| Surge protection [kV]: | 10 | Technical Warranty: | 5 with the possibility of extension to 10 |
| Diffuser material: | tempered glass | ENEC Certificate: | 0351/ENEC/24/M1; 0121/ENEC+/24/M2 |
| Diffuser type: | transparent | CE certificate: | 03/2025 |
| Optics material: | PMMA + PC | Zhaga-D4i: | ZG430121062024 |
| Optics: | RM7 | Environmental Product Declaration (EPD): | 683/2024 |
| Exchangeable source: | yes | Manual: | Download PDF |

LIGHT CURVES



SKVER S Z1 3450LM 740 RM7 MF IP66 II CL. DALI B 0 (23W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|---------------------|
| 435461 | SKVER cover fi 48mm |
| 435478 | SKVER cover fi 60mm |

Card creation date: 12 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 03/2025



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl