

# SKVER S Z1 6850LM 740 RM7 WJ IP66 II CL. DALI B 0 (47W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	803475
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	47
<b>Luminous flux [lm]*:</b>	6850
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	70
<b>Electrical protection class:</b>	II
<b>Optics:</b>	RM7
<b>Control:</b>	Yes + 5-stage power reduction

## CHARACTERISTICS

**Skver LED S (Z1 WJ)** modular, equipped with an adjustable bracket, innovative park and city LED luminaire with tool-free access to the equipment compartment, equipped with a tool-free service plate compliant with the ZhagaBook 13 and 15 standard, adapted for both top and boom mounting. Made of pressure-formed aluminum, equipped with a lampshade made of PC, characterized by maximum resistance to mechanical impacts and an increased color rendering index. The luminaire is available in variants with an omnidirectional and directed way of lighting. The luminaire allows the use of dedicated functional accessories in the form of a screen limiting disturbing glare.

## APPLICATION

Skver LED S (Z1 WJ) is ideal for biologically active spaces, parks, squares, urban green islands, urban interiors consistent with the photometric project, pedestrian routes, housing estate roads, parking lots and garden layouts. The Z1 WJ variant is suitable for lighting parks and streets in accordance with the M4 and M5 class standards, while the Z2 WJ variant is perfect for urban infrastructure instances, where optimal service time and the possibility of performing service without dismantling the entire luminaire are key.

# SKVER S Z1 6850LM 740 RM7 WJ IP66 II CL. DALI B 0 (47W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	803475	<b>Material of the body:</b>	powder coated aluminium
<b>EAN:</b>	5905963803475	<b>Colour of the body:</b>	black
<b>Category type:</b>	Park and city lighting	<b>Dimensions (H/W/T/S) [mm]:</b>	461/360/216
<b>Version:</b>	S	<b>Mounting dimensions [mm]:</b>	ø60
<b>Light source:</b>	LED module	<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]:</b>	47	<b>Ingress protection:</b>	IP66
<b>Supply voltage [V]:</b>	220-240	<b>Mounting version:</b>	Top, on pole / Side, on boom
<b>Frequency [Hz]:</b>	47-63	<b>Working temperature [°C]:</b>	from -40 to +50
<b>Luminous flux [lm]:</b>	6850	<b>DIMM DALI:</b>	yes
<b>Luminous efficacy [lm/W]:</b>	152	<b>Control:</b>	Yes + 5-stage power reduction
<b>Energy efficiency class:</b>	C	<b>Protection type:</b>	NTC
<b>Electrical protection class:</b>	II	<b>Net weight [kg]:</b>	5.400
<b>Colour temperature [K]:</b>	4000	<b>Wire type:</b>	HO7 RNF-2x1
<b>Color rendering index (Ra) &gt;:</b>	70	<b>Photobiological safety:</b>	RG0 - exempt (no photobiological hazard)
<b>Power factor:</b>	0.96	<b>Technical Warranty:</b>	5 with the possibility of extension to 10
<b>Surge protection [kV]:</b>	10	<b>ENEC Certificate:</b>	<a href="#">0351/ENEC/24/M1;</a> <a href="#">0121/ENEC+/24/M2</a>
<b>Diffuser material:</b>	tempered glass	<b>CE certificate:</b>	<a href="#">04/2025</a>
<b>Diffuser type:</b>	transparent	<b>Zhaga-D4i:</b>	<a href="#">ZG430121062024</a>
<b>Optics material:</b>	PMMA + PC	<b>Environmental Product Declaration (EPD):</b>	<a href="#">683/2024</a>
<b>Optics:</b>	RM7	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Exchangeable source:</b>	yes	<b>LED lifespan L95B10 [h]:</b>	100000

# SKVER S Z1 6850LM 740 RM7 WJ IP66 II CL. DALI B 0 (47W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
435461	SKVER cover fi 48mm
435478	SKVER cover fi 60mm

Card creation date: 12 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 04/2025



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl