

LABO LED PAR SM 128W 4000K 596X1196 MM

DETAILED CARD



TECHNICAL PARAMETERS

Index:	259043
Ingress protection:	IP65
Impact resistance:	IK07
Nominal power [W]:	128
Luminous flux [lm]*:	10250
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	F
Material of the body:	powder coated steel
Diffuser material:	PMMA

CHARACTERISTICS

Fitting with high ingress protection class IP65, suitable for surface and flush mounting in modular ceilings. It is equipped with patented HE reflector which reduces the effect of glare. Available with prismatic or opal diffuser. Option with a color rendering index CRI (Ra)>90 available on request.

APPLICATION

Luminaire intended for indoor use in medical and laboratory rooms as well as in industrial facilities (especially in food, pharmaceuticals, cosmetics), where you need high ingress protection class and the highest lighting parameters.

CRI(Ra) >90 (on request)

CRI index (Ra) is a factor determining the degree of color rendering. The higher the value, the more natural the colors. Ra>90 means comfort for the eyes and greater ability to recognize colors and their shades. Fittings with such a high rate are used in rooms where high accuracy in color rendering is required (operating rooms, surgeries).


LABO LED PAR SM 128W 4000K 596X1196 MM

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	259043	Material of the body:	powder coated steel
Light source:	LED module	Colour of the body:	white
Nominal power [W]:	128	Dimensions (H/W/T/S) [mm]:	1195/595/50
Rated power of the luminaire [W]:	134.30	Impact resistance:	IK07
Supply voltage [V]:	220-240	Ingress protection:	IP65
Frequency [Hz]:	50 - 60	Mounting version:	recessed
Luminous flux [lm]:	10250	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	76	Net weight [kg]:	14.500
Energy efficiency class:	F	Warranty [years]:	5
Electrical protection class:	I	EAN:	5905963259043
Colour temperature [K]:	4000	Category type:	louvres
Colour rendering index:	>80	ETIM class:	EC002892
SDCM:	≤ 3	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	50000	CE certificate:	255/2023
Diffuser material:	PMMA	PZH certificate:	B-BK-60212-0111/21
Diffuser type:	transparent	Warranty [years]:	5
Optics:	HE	Manual:	Download PDF

LIGHT CURVES



LABO LED PAR SM 128W 4000K 596X1196 MM

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
999543	Plasterboard recessing kit 630x630 white (steel version)



Plasterboard recessing kit 630x630
white (steel version) (999543)

Card creation date: 06 December 2018

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 255/2023