

# SKVER S R 5400LM 740 RM7 MF IP66 II CL. DALI ZG B 0 (39W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	768828
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK10
<b>Rated power of the luminaire [W]*:</b>	39
<b>Luminous flux [lm]*:</b>	5400
<b>Colour temperature [K]:</b>	4000
<b>Colour rendering index:</b>	> 70
<b>Electrical protection class:</b>	II
<b>Optics:</b>	RM7
<b>Control:</b>	Yes + 5-stage power reduction

## CHARACTERISTICS

**Skver LED S (R MF)** modular pendant innovative park-and-ride LED luminaire with tool-free access to the fixture compartment, equipped with a tool-free service plate compliant with the ZhagaBook 13 and 15 standard. Made of die-formed aluminium, equipped with a flat glass diffuser, characterised by ULR = 0, maximum resistance to mechanical impact and increased colour rendering index. The luminaire is available in both omnidirectional and directed modes. The luminaire allows the use of dedicated functional accessories to customise the luminaire, both in terms of mounting, mode of illumination and design. **Distinctive features:**\* Omnidirectional and directed spreads.\* Variants available in standard (CRI70) and enhanced colour rendering index (CRI80)\* Architectural build quality\* Highest degree of IK10 immunity\* Tool-free access to accessory compartment\* Can be fitted with a dedicated accessory: glare reduction shade.\* Can be equipped with dedicated accessories: ULR < 1 canopy, urban canopy\* Possibility to equip the luminaire with a Zhaga connector compatible with ZD4i.\* Multiple mounting options\* Certified highest utility and environmental quality: ENEC, ENEC+, ZD4i, EPD environmental declaration\* Tool-less service board, compliant with ZhagaBook13 and ZhagaBook15 standard.\* Knife connector to cut off voltage during service work\* Luminaire with ULR = 0

## APPLICATION

Biologically active space with a special role for the protection of dark skies; parks; squares; urban green islands; urban interiors according to photometric design; pedestrian routes; estate roads; car parks; garden arrangements. Various hanging standards. The R MF variant, due to its ULR = 0 parameter, protects the urban ecosystem from excessive light emission into the upper atmosphere, thus restoring dark night skies over our cities.

# SKVER S R 5400LM 740 RM7 MF IP66 II CL. DALI ZG B 0 (39W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	768828	Optics material:	PMMA + PC
Rated power of the luminaire [W]:	39	Exchangeable source:	yes
EAN:	5905963768828	Material of the body:	powder coated aluminium
Luminous flux [lm]:	5400	Colour of the body:	black
Category type:	street lighting	Dimensions (H/W/T/S) [mm]:	ø360/185
Luminous efficacy [lm/W]:	138	Mounting dimensions [mm]:	ø42
Version:	S	Impact resistance:	IK10
Energy efficiency class:	C	Ingress protection:	IP66
Light source:	LED module	Working temperature [°C]:	from -40 to +50
Colour temperature [K]:	4000	Control:	Yes + 5-stage power reduction
Colour rendering index:	> 70	Protection type:	NTC
Supply voltage [V]:	220-240	ULOR:	0%
Electrical protection class:	II	Technical Warranty:	5 with the possibility of extension to 10
Frequency [Hz]:	50 - 60	ENEC Certificate:	<a href="#">0351/ENEC/24/M1</a> ; <a href="#">0121/ENEC+/24/M2</a>
Optics:	RM7	CE certificate:	<a href="#">10/2025</a>
DIMM DALI:	yes	Zhaga-D4i:	<a href="#">ZG430121062024</a>
Power factor:	0.99	Environmental Product Declaration (EPD):	<a href="#">683/2024</a>
Surge protection [kV]:	10	Manual:	<a href="#">Download PDF</a>
Diffuser material:	toughened glass	LED lifespan L95B10 [h]:	100000
Diffuser type:	transparent		

# SKVER S R 5400LM 740 RM7 MF IP66 II CL. DALI ZG B 0 (39W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
435515	SKVER Backshield RAL9005
435522	SKVER Hood example 1 RAL9005
449017	Drilling pattern
804427	SKVER R male adapter thread M20x40 (pitch 2.5)
804328	SKVER R male adapter thread ¾ inch x 40 (gas)
804434	SKVER R male adapter thread 1 inch x40 (gas)
804335	SKVER R female adapter thread ¾ inch x 40 (gas)
804441	SKVER R female adapter thread 1 inch x40 (gas)



SKVER Backshield RAL9005 (435515)



SKVER Hood example 1 RAL9005 (435522)



Drilling pattern (449017)



SKVER R male adapter thread M20x40 (pitch 2.5) (804427)



SKVER R male adapter thread ¾ inch x 40 (gas) (804328)



SKVER R male adapter thread 1 inch x40 (gas) (804434)



SKVER R female adapter thread ¾ inch x 40 (gas) (804335)



SKVER R female adapter thread 1 inch x40 (gas) (804441)

Card creation date: 24 April 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 10/2025