

TUBA IP69K PMMA 630MM 6250LM 840 DALI 120D IK05 36W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	772061
Ingress protection:	IP69K
Impact resistance:	IK05
Rated power of the luminaire [W]*:	36
Luminous flux [lm]*:	6250
Colour temperature [K]:	4000
Colour rendering index:	>80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	B

CHARACTERISTICS

Tuba IP69K is a cylindrical luminaire for special tasks - where other solutions fail. Designed for extreme conditions, it combines superior sealing, chemical resistance and mechanical durability. Meeting the standard for IP69K means full protection against dust (IP6X) and complete resistance to water at extremely high pressure (100 bar) at 80°C (IPX9K). This makes the luminaire ideal for areas requiring intensive cleaning, including with powerful water jets and detergents. The IP69K tube is designed to operate in the most demanding conditions. Made from chemically resistant materials: PMMA and extremely resistant borosilicate glass - ensuring exceptional durability even in aggressive industrial environments. The turned acid-resistant steel endcap eliminates the risk of corrosion, and its resistance to ammonia and zoonotic gases makes it ideal for livestock and processing facilities. Thanks to the decompression valve, the luminaire easily withstands rapid temperature changes, and the highest IK10 impact resistance rating (for the PC version) guarantees reliability in the harshest operating conditions. The IP69K tube achieves up to 194 lm/W, meeting the requirements of the highest energy class A. Through-beam versions, different lens distributions and two lengths (630 and 1220 mm) are available. In addition, versions with UGR<19, UGR<22, UGR<25 provide visual comfort even in demanding applications. Minimalist design, ease of installation and cleanliness make the Tuba IP69K a reliable and timeless solution.

APPLICATION

Ideal for areas requiring regular high-pressure cleaning, such as car washes, sewage treatment plants, food processing plants or slaughterhouses. It excels in environments with high humidity, sub-zero temperatures and aggressive fumes - from cold stores and freezers to mushroom, animal and plant farms. Thanks to its superior chemical and mechanical resistance, it is a reliable solution for workshops and service channels. It is also ideal for industrial halls, traffic routes and even as minimalist, decorative general lighting in commercial buildings.

TUBA IP69K PMMA 630MM 6250LM 840 DALI 120D IK05 36W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	36	Surge protection [kV]:	1
Index:	772061	Diffuser colour:	transparent
Colour temperature [K]:	4000	DIMM DALI:	yes
EAN:	5905963772061	Material of the body:	stal nierdzewna
Luminous flux [lm]:	6250	Through wiring:	LS1
Light source:	LED module	Cable length [m]:	1.50
Impact resistance:	IK05	Dimensions (H/W/T/S) [mm]:	660/64.5
Diffuser material:	PMMA	Mounting dimensions [mm]:	602.5
Supply voltage [V]:	220-240	Ingress protection:	IP69K
Beam angle [°]:	120	Mounting version:	surface, suspended
Frequency [Hz]:	50-60	Working temperature [°C]:	35
Light distribution type:	symmetric	Tilt angle adjustment [°]:	yes
Luminous efficacy [lm/W]:	174	Wire type:	H05VV-F 5X0,75
Energy efficiency class:	B	Accessories included:	surface-mounted bracket
Electrical protection class:	I	Number on the palette [pcs]:	154
Colour rendering index:	>80	Net weight [kg]:	2.100
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	125000	CE certificate:	11/2025
LED lifespan L80B20 [h]:	80000	Manual:	Download PDF
LED lifespan L90B10 [h]:	38000		

TUBA IP69K PMMA 630MM 6250LM 840 DALI 120D IK05 36W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
778254	Tuba IP69K 3P connector set
778261	Connector set Tuba IP69K 5P DALI



Tuba IP69K 3P connector set (778254)



Connector set Tuba IP69K 5P DALI (778261)

Card creation date: 17 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 11/2025