

TUBA IP69K PMMA 630MM 5150LM 840 LS2 (1F) SN IK05 32W

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|------------------------------------|--------|
| Index: | 776021 |
| Ingress protection: | IP69K |
| Impact resistance: | IK05 |
| Rated power of the luminaire [W]*: | 32 |
| Luminous flux [lm]*: | 5150 |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | 80 |
| SDCM: | ≤ 3 |
| Electrical protection class: | I |
| Energy efficiency class: | B |

CHARACTERISTICS

Tuba IP69K is a cylindrical luminaire for special tasks - where other solutions fail. Designed for extreme conditions, it combines superior sealing, chemical resistance and mechanical durability. Meeting the standard for IP69K means full protection against dust (IP6X) and complete resistance to water at extremely high pressure (100 bar) at 80°C (IPX9K). This makes the luminaire ideal for areas requiring intensive cleaning, including with powerful water jets and detergents. The IP69K tube is designed to operate in the most demanding conditions. Made from chemically resistant materials: PMMA and extremely resistant borosilicate glass - ensuring exceptional durability even in aggressive industrial environments. The turned acid-resistant steel endcap eliminates the risk of corrosion, and its resistance to ammonia and zoonotic gases makes it ideal for livestock and processing facilities. Thanks to the decompression valve, the luminaire easily withstands rapid temperature changes, and the highest IK10 impact resistance rating (for the PC version) guarantees reliability in the harshest operating conditions. The IP69K tube achieves up to 194 lm/W, meeting the requirements of the highest energy class A. Through-beam versions, different lens distributions and two lengths (630 and 1220 mm) are available. In addition, versions with UGR<19, UGR<22, UGR<25 provide visual comfort even in demanding applications. Minimalist design, ease of installation and cleanliness make the Tuba IP69K a reliable and timeless solution.

APPLICATION

Ideal for areas requiring regular high-pressure cleaning, such as car washes, sewage treatment plants, food processing plants or slaughterhouses. It excels in environments with high humidity, sub-zero temperatures and aggressive fumes - from cold stores and freezers to mushroom, animal and plant farms. Thanks to its superior chemical and mechanical resistance, it is a reliable solution for workshops and service channels. It is also ideal for industrial halls, traffic routes and even as minimalist, decorative general lighting in commercial buildings.

TUBA IP69K PMMA 630MM 5150LM 840 LS2 (1F) SN IK05 32W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|------------------------------|------------------------------|
| Index: | 776021 | Optics: | matrix lens |
| EAN: | 5905963776021 | Optics material: | PC |
| Light source: | LED module | Material of the body: | stainless steel |
| Rated power of the luminaire [W]: | 32 | Dimensions (H/W/T/S) [mm]: | 697/64.5 |
| Luminous flux [lm]: | 5150 | Mounting dimensions [mm]: | 602.5 |
| Supply voltage [V]: | 220-240 | Impact resistance: | IK05 |
| Frequency [Hz]: | 50-60 | Ingress protection: | IP69K |
| Luminous efficacy [lm/W]: | 161 | Mounting version: | surface, suspended |
| Energy efficiency class: | B | Working temperature [°C]: | from -25 to +35 |
| Electrical protection class: | I | Tilt angle adjustment [°]: | yes |
| Colour temperature [K]: | 4000 | Wire type: | H07RN-F 3x1,5 |
| Colour rendering index: | 80 | Through wiring: | LS2 |
| SDCM: | ≤ 3 | Remarks: | Cable length 2 x 1.4m |
| LED lifespan L70B50 [h]: | 126000 | Accessories included: | surface-mounted bracket |
| LED lifespan L80B20 [h]: | 80000 | Number on the palette [pcs]: | 154 |
| LED lifespan L90B10 [h]: | 38000 | Net weight [kg]: | 2.500 |
| Beam angle [°]: | 65 | Light distribution type: | SN |
| Surge protection [kV]: | 2 | Warranty [years]: | 5 |
| Diffuser material: | PMMA | CE certificate: | 11/2025 |
| Diffuser colour: | transparent | Manual: | Download PDF |

TUBA IP69K PMMA 630MM 5150LM 840 LS2 (1F) SNIK05 32W

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|----------------------------------|
| 778254 | Tuba IP69K 3P connector set |
| 778261 | Connector set Tuba IP69K 5P DALI |



Tuba IP69K 3P connector set (778254)



Connector set Tuba IP69K 5P DALI (778261)