TUBA IP69K PC 1220MM 9400LM 840 SA IK10 59W

DETAILED CARD





TECHNICAL PARAMETERS

Index:	77784
Ingress protection:	IP69K
Impact resistance:	IK10
Rated power of the luminaire [W]*:	59
Luminous flux [lm]*:	9400
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	1
Energy efficiency class:	В

CHARACTERISTICS

Tuba IP69K is a cylindrical luminaire for special tasks - where other solutions fail. Designed for extreme conditions, it combines superior sealing, chemical resistance and mechanical durability. Meeting the standard for IP69K means full protection against dust (IP6X) and complete resistance to water at extremely high pressure (100 bar) at 80°C (IPX9K). This makes the luminaire ideal for areas requiring intensive cleaning, including with powerful water jets and detergents. The IP69K tube is designed to operate in the most demanding conditions. Made from chemically resistant materials: PMMA and extremely resistant borosilicate glass - ensuring exceptional durability even in aggressive industrial environments. The turned acid-resistant steel endcap eliminates the risk of corrosion, and its resistance to ammonia and zoonotic gases makes it ideal for livestock and processing facilities. Thanks to the decompression valve, the luminaire easily withstands rapid temperature changes, and the highest IK10 impact resistance rating (for the PC version) guarantees reliability in the harshest operating conditions. The IP69K tube achieves up to 194 lm/W, meeting the requirements of the highest energy class A. Through-beam versions, different lens distributions and two lengths (630 and 1220 mm) are available. In addition, versions with UGR<19, UGR<22, UGR<25 provide visual comfort even in demanding applications. Minimalist design, ease of installation and cleanliness make the Tuba IP69K a reliable and timeless solution.

APPLICATION

Ideal for areas requiring regular high-pressure cleaning, such as car washes, sewage treatment plants, food processing plants or slaughterhouses. It excels in environments with high humidity, sub-zero temperatures and aggressive fumes from cold stores and freezers to mushroom, animal and plant farms. Thanks to its superior chemical and mechanical resistance, it is a reliable solution for workshops and service channels. It is also ideal for industrial halls, traffic routes and even as minimalist, decorative general lighting in commercial buildings.



TUBA IP69K PC 1220MM 9400LM 840 SA IK10 59W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

777844
5905963777844
LED module
59
9400
220-240
50-60
159
В
I
4000
80
3
132000
83000
40000
asymetric
2
PC
transparent
matrix lens

Material of the body: stainless steel Dimensions (H/W/T/S) [mm]: 1250/64.5 Mounting dimensions [mm]: 1195.5 Impact resistance: IK10 Ingress protection: IP69K Mounting version: surface, suspended Working temperature [°C]: from -25 to +35 Tilt angle adjustment [°]: yes Wire type: H07RN-F 3x1,5 Through wiring: LS1 Remarks: Cable length 1.4m Accessories included: surface-mounted bracket Number on the palette [pcs]: 98 Net weight [kg]: 2.800 Light distribution type: SA Warranty [years]: 5 CE certificate: 11/2025 Manual: Download Plik LDT: Download	Optics material:	PC
Mounting dimensions [mm]: Impact resistance: Ingress protection: Mounting version: Working temperature [°C]: Tilt angle adjustment [°]: Wire type: H07RN-F 3x1,5 LS1 Remarks: Cable length 1.4m Accessories included: Number on the palette [pcs]: Net weight [kg]: Light distribution type: Manual: Mi195.5 IK10 IP69K IP69K IN10 IP69K I	Material of the body:	stainless steel
Impact resistance: Ingress protection: Mounting version: Working temperature [°C]: Tilt angle adjustment [°]: Wire type: Through wiring: Remarks: Accessories included: Number on the palette [pcs]: Net weight [kg]: Light distribution type: Manual: Mounting Version: Surface, suspended from -25 to +35 yes H07RN-F 3x1,5 LS1 Cable length 1.4m surface-mounted bracket Surface-mounted bracket Sa 2.800 Light distribution type: SA Warranty [years]: Download PDF	Dimensions (H/W/T/S) [mm]:	1250/64.5
Ingress protection: Mounting version: Working temperature [°C]: Tilt angle adjustment [°]: Wire type: H07RN-F 3x1,5 Through wiring: LS1 Remarks: Cable length 1.4m Accessories included: Number on the palette [pcs]: Net weight [kg]: Light distribution type: SA Warranty [years]: CE certificate: Manual: Download PDF	Mounting dimensions [mm]:	1195.5
Mounting version: Working temperature [°C]: Tilt angle adjustment [°]: Wire type: H07RN-F 3x1,5 LS1 Remarks: Cable length 1.4m Accessories included: Number on the palette [pcs]: Net weight [kg]: Light distribution type: SA Warranty [years]: CE certificate: Manual: Surface, suspended From -25 to +35 yes LS1 LS1 Cable length 1.4m Surface-mounted bracket 98 SA 5 CE certificate: 11/2025 Download PDF	Impact resistance:	IK10
Working temperature [°C]: Tilt angle adjustment [°]: Wire type: H07RN-F 3x1,5 Through wiring: LS1 Remarks: Cable length 1.4m Accessories included: Number on the palette [pcs]: Net weight [kg]: Light distribution type: SA Warranty [years]: CE certificate: 11/2025 Manual:	Ingress protection:	IP69K
Tilt angle adjustment [°]: Wire type: H07RN-F 3x1,5 Through wiring: LS1 Remarks: Cable length 1.4m Accessories included: Number on the palette [pcs]: Net weight [kg]: Light distribution type: SA Warranty [years]: CE certificate: Manual: yes yes yes 1028 407RN-F 3x1,5 280 280 2800 58 400 58 400 59 500 500 500 500 500 500	Mounting version:	surface, suspended
Wire type: H07RN-F 3x1,5 Through wiring: LS1 Remarks: Cable length 1.4m Accessories included: surface-mounted bracket Number on the palette [pcs]: 98 Net weight [kg]: 2.800 Light distribution type: SA Warranty [years]: 5 CE certificate: 11/2025 Manual: Download PDF	Working temperature [°C]:	from -25 to +35
Through wiring: Remarks: Cable length 1.4m Accessories included: Surface-mounted bracket Number on the palette [pcs]: 98 Net weight [kg]: 2.800 Light distribution type: SA Warranty [years]: 5 CE certificate: 11/2025 Manual: Download PDF	Tilt angle adjustment [°]:	yes
Remarks: Cable length 1.4m surface-mounted bracket Number on the palette [pcs]: 98 Net weight [kg]: Light distribution type: Warranty [years]: CE certificate: 11/2025 Manual: Cable length 1.4m Surface-mounted bracket 98 2.800 SA 5 CE contificate: 11/2025 Download PDF	Wire type:	H07RN-F 3x1,5
Accessories included: Number on the palette [pcs]: Net weight [kg]: Light distribution type: SA Warranty [years]: CE certificate: Manual: Surface-mounted bracket 98 2.800 SA 5 CD Download PDF	Through wiring:	LS1
Number on the palette [pcs]: 98 Net weight [kg]: 2.800 Light distribution type: SA Warranty [years]: 5 CE certificate: 11/2025 Manual: Download PDF	Remarks:	Cable length 1.4m
Net weight [kg]: Light distribution type: SA Warranty [years]: CE certificate: 11/2025 Manual: Download PDF	Accessories included:	surface-mounted bracket
Light distribution type: Warranty [years]: CE certificate: Manual: Download PDF	Number on the palette [pcs]:	98
Warranty [years]: 5 CE certificate: 11/2025 Manual: Download PDF	Net weight [kg]:	2.800
CE certificate: 11/2025 Manual: Download PDF	Light distribution type:	SA
Manual: Download PDF	Warranty [years]:	5
	CE certificate:	11/2025
Plik LDT: <u>Download</u>	Manual:	Download PDF
	Plik LDT:	Download



TUBA IP69K PC 1220MM 9400LM 840 SA IK10 59W

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
778254	Tuba IP69K 3P connector set
778261	Connector set Tuba IP69K 5P DALI





Tuba IP69K 3P connector set (778254)

Connector set Tuba IP69K 5P DALI (778261)

Card creation date: 17 February 2025



