

# DIRECTO S M 3H AT

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	897221
<b>Ingress protection:</b>	IP20
<b>Nominal power [W]:</b>	3
<b>Electrical protection class:</b>	II
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PMMA
<b>Emergency lighting [h]:</b>	3
<b>Battery:</b>	NiCd
<b>Operating mode:</b>	M/NM
<b>Autotest:</b>	yes

## CHARACTERISTICS

Surface-mounted emergency fitting, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery with manual testing function included, the battery life in the event of an emergency is 3h. A wide range of optional accessories available - Recessed mounting set, Flag mounting bracket, Suspended mounting set.

## APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.

# DIRECTO S M 3H AT

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	897221	<b>Battery:</b>	NiCd
<b>Nominal power [W]:</b>	3	<b>Battery capacity [mAh]:</b>	900
<b>Light source:</b>	LED module	<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	PMMA	<b>Dimensions (H/W/T/S) [mm]:</b>	255/199
<b>Emergency lighting [h]:</b>	3	<b>Ingress protection:</b>	IP20
<b>Operating mode:</b>	M/NM	<b>Mounting version:</b>	surface
<b>Supply voltage [V]:</b>	220-240	<b>Working temperature [°C]:</b>	od 10 do +40
<b>Autotest:</b>	yes	<b>Category type:</b>	emergency lighting
<b>Frequency [Hz]:</b>	50-60	<b>Warranty [years]:</b>	2
<b>Electrical protection class:</b>	II	<b>CE certificate:</b>	<a href="#">14/2025</a>
<b>LED lifespan L70B50 [h]:</b>	50000	<b>Manual:</b>	Download PDF

# DIRECTO S M 3H AT

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
897238	DIRECTO S suspended mounting kit
897245	DIRECTO S Flag Mounting Kit
897252	DIRECTO S Recessed Mounting Kit



DIRECTO S suspended mounting kit (897238)



DIRECTO S Flag Mounting Kit (897245)



DIRECTO S Recessed Mounting Kit (897252)

Card creation date: 18 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 14/2025