

# DIRECTO S M 3H AT

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	897221
Ingress protection:	IP20
Nominal power [W]:	3
Electrical protection class:	II
Diffuser material:	PC
Diffuser type:	PMMA
Emergency lighting [h]:	3
Battery:	NiCd
Operating mode:	M/NM
Autotest:	yes

## CHARACTERISTICS

Surface-mounted emergency fitting, available in maintained and non-maintained versions. The body is made of polycarbonate; PMMA mounting board. NiCd battery with manual testing function included, the battery life in the event of an emergency is 3h. A wide range of optional accessories available - Recessed mounting set, Flag mounting bracket, Suspended mounting set.

## APPLICATION

The main task of the independent emergency light fitting is to indicate the direction of evacuation routes and emergency exits after a power outage, i.e. in Safe Mode. Suitable for wall or ceiling mounting. Especially recommended for technical rooms (corridors, stairways, garages, basements) where permanent emergency lighting is required.

# DIRECTO S M 3H AT

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	897221	Ingress protection:	IP20
Light source:	LED module	Mounting version:	surface
Nominal power [W]:	3	Working temperature [°C]:	od 10 do +40
Supply voltage [V]:	220-240	Emergency lighting [h]:	3
Frequency [Hz]:	50-60	Category type:	emergency lighting
Electrical protection class:	II	Autotest:	yes
LED lifespan L70B50 [h]:	50000	Operating mode:	M/NM
Battery:	NiCd	Warranty [years]:	2
Battery capacity [mAh]:	900	CE certificate:	<a href="#">14/2025</a>
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	PMMA	Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	255/199		

# DIRECTO S M 3H AT

DETAILED CARD

## ACCESSORIES AVAILABLE


index	Name
897238	DIRECTO S suspended mounting kit
897245	DIRECTO S Flag Mounting Kit
897252	DIRECTO S Recessed Mounting Kit



DIRECTO S suspended mounting kit (897238)



DIRECTO S Flag Mounting Kit (897245)



DIRECTO S Recessed Mounting Kit (897252)