

# FACTOR LED 1M 29700LM 740 PP1 DALI IP66 SH (233W) C5-M

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	682186
<b>Ingress protection:</b>	IP66
<b>Impact resistance:</b>	IK09
<b>Rated power of the luminaire [W]*:</b>	233
<b>Luminous flux [lm]*:</b>	29700
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	70
<b>SDCM:</b>	5
<b>Electrical protection class:</b>	I
<b>Energy efficiency class:</b>	D

## CHARACTERISTICS

Factor Led C5-M (corrosion protection in harsh industrial and marine environments) is the latest generation of high-powered floodlight with impressive lumen output. It is characterised not only by very high luminous efficiency, but also by high IP66 sealing and IK09 impact resistance. These parameters were achieved thanks to the branded components used, the robust housing made of cast aluminium LM-6 (aluminium-silicon alloy) and the use of a passive lamp cooling system, which allows excess heat generation to be dissipated during lamp operation. In the C5-M version, the paint coating plays an even more important role. The Factor Led has the advantage of being very quick and easy to install. The lightweight steel arm is attached to the supporting structure (wall, column) and then the light modules are plugged in. On one bracket, the installer can plug in a lamp containing 1 to 4 such modules.

## APPLICATION

Ports, wharves, shipyards, oil rigs and offshore infrastructure, chemical industry and refineries, bridges and infrastructure exposed to marine conditions, lighting on ships and ferries, industrial areas, playing fields, airports, car parks with high humidity and salinity.


# FACTOR LED 1M 29700LM 740 PP1 DALI IP66 SH (233W) C5-M

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	682186	Colour of the body:	RAL7016
EAN:	5905963682186	Dimensions (H/W/T/S) [mm]:	191/425/217
Light source:	LED module	Mounting dimensions [mm]:	230
Rated power of the luminaire [W]:	233	Impact resistance:	IK09
Luminous flux [lm]:	29700	Ingress protection:	IP66
Supply voltage [V]:	100-277	Mounting version:	top
Frequency [Hz]:	47-63	Working temperature [°C]:	from -40 to +45
Luminous efficacy [lm/W]:	127	DIMM DALI:	yes
Energy efficiency class:	D	Dimensions of single box [mm]:	430
Electrical protection class:	I	Number on the palette [pcs]:	35
Colour temperature [K]:	4000	Net weight [kg]:	5.790
Color rendering index (Ra) >:	70	Version:	1 module
SDCM:	5	Light distribution type:	PP1
Power factor:	0.97	Corrosivity category:	C5-M
LED lifespan L70B50 [h]:	156000	Warranty [years]:	5
LED lifespan L80B10 [h]:	98000	CE certificate:	<a href="#">262/2023</a>
LED lifespan L90B10 [h]:	47000	ENEC Certificate:	<a href="#">0404/ENEC/25</a>
Beam angle [°]:	PP1	Environmental Product Declaration (EPD):	<a href="#">816/2025</a>
Surge protection [kV]:	6	Manual:	<a href="#">Download PDF</a>
Diffuser material:	tempered glass	Plik LDT:	<a href="#">Download</a>
Material of the body:	aluminium		

## LIGHT CURVES



# FACTOR LED 1M 29700LM 740 PP1 DALI IP66 SH (233W) C5-M

DETAILED CARD

## TECHNICAL PICTURES



Card creation date: 19 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 262/2023